## 48 INCHES LENGTH



Connector A 112160 BNC Jack Straight Brass Nickel 50 Ohm RG-174 Continuity/Hi-Pot Connector B 112234 BNC Jack Straight Bulkhead - Rear Mount Brass Nickel

## Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

		Connector A	l l	Cable			Connector B		
D T B C P In M B B I F	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: mpedance: Mounting: Body Material: Body Finish: P Rating:	112160 BNC JK RG174 R BNC Jack Straight Solder Standard 50 Ohm Cable Brass Nickel None	RG316 LMR100 500 Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	Cable RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 48 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material:	112234 BNC Clamp BHD JH BNC Jack Straight Crimp Standard 50 Ohm Bulkhead - Rear Mo Brass Nickel None			
C	Contact Material: Contact Finish: Max. Freq.: Booting:	Beryllium Copper Silver 4 GHz BNC Jack Straigh	t			Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	Beryllium Copper Silver 4 GHz BNC Jack Straight E 0°	ЗНD	
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT DO NOT CODY CUSTOM CABLE IN CONTROLLED DOCUMENT			THIS DRAWING MAY CONTAIN PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIMEN INC. IT MAY NOT BE REPRODU IN ANY FORM WITHOUT THE V CUSTOM CABLE INC. ACCEPT/ ESTABLISHES AND AGREEMEN	AND MUST NOT BE U ITAL TO CUSTOM CAI JCED OR TRANSCRIBI WRITTEN CONSENT O ANCE OF THIS DRAWI	BLE ED F NG Part No:	BNC-ST-JK/BNC-ST-JK G174 48I		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	