



Enter keywords or part number

[What's New](#) | [Products](#) | [Solutions](#) | [Design](#) | [AppNotes](#) | [Support](#) | [Sales](#) | [About Us](#) | [Members](#)
[Maxim](#) > [Products](#) > [\[Power and Battery Management\]](#) [\[Automotive\]](#)

MAX15034BEVKIT

Evaluation Kit for the MAX15034B and MAX5066

[QuickView](#) | [Technical Documents](#) | [Ordering Info](#) | [More Information](#) | [User Comments \(0\)](#) | [All](#)

Status

Active: In Production.

Description

The MAX15034B evaluation kit (EV kit) is a two-phase, dual-output buck converter with a 5V to 16V input voltage range. The MAX15034B EV kit provides dual 1.2V output voltages (V_{OUT1} and V_{OUT2}). It delivers up to 20A output current for each output with 86.7% efficiency. The MAX15034B EV kit uses average current-mode control and operates at 300kHz switching frequency per phase where each phase is 180° out-of-phase with respect to the other.

[Request Full Data Sheet](#)

The MAX15034B EV kit is a fully assembled and tested circuit board. Both outputs are adjustable between 0.61V and 5.5V by changing feedback resistors R4–R7. Additional features include thermal-shutdown and "hiccup-mode" short-circuit protection.

Key Features

- 5V to 16V Input-Voltage Range (Design Optimized for 12V Input)
- Output Voltages
 - 1.2V at 20A (Adjustable from 0.61V to 5.5V)
 - 1.2V at 20A (Adjustable from 0.61V to 5.5V)
- 300kHz Switching Frequency
- Both Outputs Can be Paralleled for Higher Current Capability (Using Mode Function)
- Average Current-Mode Control Provides Accurate Current Limit
- Current-Sharing Accuracy within $\pm 5\%$ Between Parallel Channels
- 180° Interleaved Operation Reduces Size of Input Filter Capacitors
- Overtemperature Shutdown
- Excellent Line- and Load-Transient Response
- Hiccup-Mode Overcurrent Protection
- Can be Synchronized to an External Clock
- Provision for Output DC Accuracy
- Low-Profile Components
- Fully Assembled and Tested

Applications/ Uses

- Graphics Cards
- High-End Computers/Workstations/Servers
- Networking Systems
- Point-of-Load High-Current/High-Density Telecom DC-DC Regulators
- RAID Systems

Didn't Find What You Need?

- [Next Day Product Selection Assistance from Applications Engineers](#)
- [Parametric Search](#)
- [Applications Help](#)

QuickView

Description
Key Features
Applications/Uses
Key Specifications
Diagram

Technical Documents

Data Sheet
Application Notes
[Design Guides](#)
Engineering Journals
Reliability Reports
Software/Models
Evaluation Kits

Ordering Info

Price and Availability
Samples
[Buy Online](#)
[Package Information](#)
[Lead-Free Information](#)

More Information

[Related Products](#)
Notes and Comments
Evaluation Kits

Document Ref.: 19-4885; Rev 0; 2009-10-19
This page last modified: 2009-10-21