

## Fuse - VF-SI/TR5/2AT - 2900996

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in fuse (TR5<sup>®</sup>), nominal current: 2 A, tripping characteristic: slow-blow (T), packing volume per unit: 8 pcs.

The figure shows the 1AT version

### Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	10.0 g
Custom tariff number	85361010
Country of origin	China

### Technical data

#### General

Nominal voltage $U_N$	$\leq 250$ V AC/DC
Fuse	2 A Slow-blow

### Classifications

#### eCl@ss

eCl@ss 4.0	27142098
eCl@ss 4.1	27142098
eCl@ss 5.0	27142007
eCl@ss 5.1	27142001
eCl@ss 6.0	27142001
eCl@ss 7.0	27142001

#### ETIM

ETIM 2.0	EC000313
ETIM 3.0	EC000035
ETIM 4.0	EC000035
ETIM 5.0	EC001423

## Fuse - VF-SI/TR5/2AT - 2900996

### Classifications

#### UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421

### Approvals

#### Approvals

---

#### Approvals

EAC

---

#### Ex Approvals

---

#### Approvals submitted

---

### Approval details

EAC
-----

---