



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₂	REVISED	10/18/87	[Signature]
B	PER EC 0U20-0116-01-03	16NOV01	C. Hoang 16NOV01

COUPLING NUT SLIDE ASS'Y	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	ELECTRO-POLISHED
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35
CONTACT EXT.	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
CENTER CONTACT	BRASS PER ASTM-B-16, HALF HARD	GOLD PLATE PER MIL-G-45204
COMPONENT	MATERIAL	FINISH

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY	DATE	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
	CHECKED BY		
	APPRD BY		
FRAC. ± 1/64	DEC. ±.005	ANGLES ± 1°	

These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASSY PROCEDURE	TITLE 7mm PRECISION TO "OSN" JACK ADAPTER	
	NO. A.P. N/A	SIZE B	CODE IDENT NO. 7482-2300-00
		SCALE 3:1	REV 01 ₂
			SHEET 1 OF 1

- NOTES:
1. CAPTURED CENTER CONTACT
 2. FREQ: DC ~ 18.0 GHz
 3. VSWR (MAX): 1.015 +.0025f(GHz)

.XXX = in
XX.X = mm (REF)

CUSTOMER DRAWING

AMP PART # 1062022-1
SHEET 1 OF 1 REV B