

Product data sheet

Specifications



PLD - Floor standing encl.polyester w/plinth open bottom 850x590x320 IP43 DIN0

NSYPLD860G

ⓘ Discontinued on: 30 June 2022

ⓘ Discontinued

Main

Range	Thalassa
Category	Enclosure
Version	PLD
Enclosure type	DIN enclosure Distribution enclosure
Nominal height	850 mm
Nominal width	590 mm
Nominal depth	320 mm
Enclosure mounting	Floor-standing
Product compatibility	Fuse 0

Complementary

Device composition	1 top part 1 bottom part 2 side part 1 rear panel 1 key lock 1 door
Body type	Sealed top and open bottom part assembled with side parts
Door type	Plain front
Number of doors	1 door(s)
Door opening side	Reversible (180 °)
Lock type	Key lock
Key number	1242 E
Accessibility for operation	Bottom Front
Removable parts	Door by hinges
Material	Polyester reinforced with fibreglass
Colour	Grey (RAL 7035)

Environment

Standards	IEC 62208
-----------	-----------

IP degree of protection	IP43 conforming to IEC 60529 (plinth type open bottom) IP54 conforming to IEC 60529 (with additional sealing kit)
IK degree of protection	IK10 conforming to IEC 62262 (plain door)
Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for storage	-35...90 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	88 cm
Package 1 Width	34.5 cm
Package 1 Length	59.5 cm
Package 1 Weight	19 kg

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Recommended replacement(s)