

Contact insert module - HC-M-03/04-MOD-BUC - 1585786

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

HEAVYCON contact insert module, socket, 3 power contacts / 4 control contacts, crimp connection



Key commercial data

Packing unit	1 PCE
Minimum order quantity	2 PCE
Weight per Piece (excluding packing)	10.62 GRM
Custom tariff number	85389099
Country of origin	Germany

Technical data

Electrical characteristics

Note	for housing HC-B6 to B48, for housing HC-ADVANCE-B6 to B24, hinged retaining frame HC-M-MHR... necessary, crimp connection, power contacts: CK 4,0-ED, control contacts: CK 1,6-ED (crimp contacts not included in scope of delivery)
Rated voltage (III/3)	830 V (power contacts)
	830 V (control contacts)
Rated current	40 A (power contacts)
	10 A (control contacts)
Rated surge voltage	8 kV (power contacts)
	8 kV (control contacts)

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

Mechanical characteristics

Conductor cross section	1.5 mm ² ... 6 mm ² (power contacts)
	0.14 mm ² ... 2.5 mm ² (control contacts)

Contact insert module - HC-M-03/04-MOD-BUC - 1585786

Technical data

Mechanical characteristics

Connection cross section AWG	16 ... 10 (power contacts)
	26 ... 14 (control contacts)
Stripping length of the individual wire	9 mm (9.6 mm (4.0 -6.0 mm ²))
	8 mm (6 mm (2,5 mm ²))
Wire diameter including insulation	5 mm (for power contacts)
Insertion/withdrawal cycles	≥ 500

General

Series	HC-M-03/04
Number of module slots	1
Connection method	Crimp connection (power contacts)
	Crimp connection (control contacts)
Inflammability class according to UL 94	V0
Pollution degree	3
Surge voltage category	III
Assembly instructions	For housing heights ≥ 52 mm. Plug-in connections may only be operated only when there is no load/voltage.
Connection	The module cannot be used simultaneously with the HC-B.-TMB-SD-IP65 and HC-B.-TMS-SD-IP65 protective covers.

Material data

Contact material	Copper alloy
Contact carrier material	PC

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440209

ETIM

ETIM 3.0	EC000438
ETIM 4.0	EC000438
ETIM 5.0	EC000438

Contact insert module - HC-M-03/04-MOD-BUC - 1585786

Classifications

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

Approvals

Approvals


Approvals


UL Recognized / GOST

Ex Approvals

Approvals submitted

Approval details

UL Recognized 	
mm ² /AWG/kcmil	18-10
Nominal voltage UN	600 V

GOST 
--

Accessories

Accessories

Assembly tool

Contact insert module - HC-M-03/04-MOD-BUC - 1585786

Accessories

Assembly tool - CK4,0-EWZ - 1662735



Contact removal tool, for rotated CK-4,0-... contacts

Removal tool - VC-EW 1,6 - 1884869



Contact removal tool, for turned and rolled CK- 1.6-... contacts

Crimp contact

Crimp contact - CK1,6-ED-0,37BU AG - 1663394



Turned 1.6 crimp contact, individual female contact, core diameter 0.14 to 0.37 mm², silver-plated

Crimp contact - CK1,6-ED-0,50BU AG - 1663404



Turned 1.6 crimp contact, individual female contact, core diameter 0.5 mm², silver-plated

Crimp contact - CK1,6-ED-0,75BU AG - 1663417



Turned 1.6 crimp contact, individual female contact, core diameter 0.75 mm², silver-plated

Contact insert module - HC-M-03/04-MOD-BUC - 1585786

Accessories

Crimp contact - CK1,6-ED-1,00BU AG - 1663420



Turned 1.6 crimp contact, individual female contact, core diameter 0.75 to 1.00 mm², silver-plated

Crimp contact - CK1,6-ED-1,50BU AG - 1663433



Turned 1.6 crimp contact, individual female contact, core diameter 1.5 mm², silver-plated

Crimp contact - CK1,6-ED-2,50BU AG - 1663446



Turned 1.6 crimp contact, individual female contact, core diameter 2.5 mm², silver-plated

Crimp contact - CK1,6-ED-0,37BU AU - 1674969



Turned 1.6 crimp contact, individual female contact, core diameter 0.14 to 0.37 mm², gold-plated

Crimp contact - CK1,6-ED-0,50BU AU - 1674480



Turned 1.6 crimp contact, individual female contact, core diameter 0.5 mm², gold-plated

Contact insert module - HC-M-03/04-MOD-BUC - 1585786

Accessories

Crimp contact - CK1,6-ED-0,75BU AU - 1672440



Turned 1.6 crimp contact, individual female contact, core diameter 0.75 mm², gold-plated

Crimp contact - CK1,6-ED-1,00BU AU - 1674943



Turned 1.6 crimp contact, individual female contact, core diameter 0.75 to 1.00 mm², gold-plated

Crimp contact - CK1,6-ED-1,50BU AU - 1674930



Turned 1.6 crimp contact, individual female contact, core diameter 1.5 mm², gold-plated

Crimp contact - CK1,6-ED-2,50BU AU - 1674985



Turned 1.6 crimp contact, individual female contact, core diameter 2.5 mm², gold-plated

Crimp contact - CK4,0-ED-1,50BU AG - 1663271



Turned 4.0 crimp contact, individual female contact, core diameter 1.50 mm², silver-plated

Contact insert module - HC-M-03/04-MOD-BUC - 1585786

Accessories

Crimp contact - CK4,0-ED-2,50BU AG - 1663284



Turned 4.0 crimp contact, individual female contact, core diameter 2.50 mm², silver-plated

Crimp contact - CK4,0-ED-4,00BU AG - 1663297



Turned 4.0 crimp contact, individual female contact, core diameter 4.00 mm², silver-plated

Crimp contact - CK4,0-ED-6,00BU AG - 1663307



Turned 4.0 crimp contact, individual female contact, core diameter 6.00 mm², silver-plated

Crimp contact - CK4,0-ED-10,00BU AG - 1586183



Turned 4.0 crimp contact, single socket contact, 10 mm² conductor cross section, silver-plated

Crimping tool

Crimping pliers - CRIMPFOX-TC 4 - 1212113



Crimping pliers, for turned contacts, 0.5 - 4.0 mm², square crimp, incl. contact support

Contact insert module - HC-M-03/04-MOD-BUC - 1585786

Accessories

Crimping pliers - CRIMPFOX-TC 10 - 1212114



Crimping pliers, for turned contacts, 6.0 - 10 mm², square crimp, incl. contact locator

Crimping pliers - CRIMPFOX-1,6/2,5-ED-4,0 - 1687419



Crimping pliers, for turned contacts, CK 1.6 ED... and CK 2.5 ED...

Fiber optics contact


Female contact - CK1,6-ED-BU-POF - 1885004



Fiber optic pin contact POF, turned, for contact carriers of CK1,6-ED... contacts


Drawings

Schematic diagram



Connector pin assignment, connection side


Diagram



Derating diagram (6 modules in HC-B 24 housing)

Contact insert module - HC-M-03/04-MOD-BUC - 1585786

Dimensioned drawing



Socket module