



Load disconnecter 3LD3, Iu 25 A Main switch 3-pole Rated operating capacity at AC-23 A at 400V 9.0kW Installation in distribution boards, Basic switch without Knob-operated mechanism

| Model | |
|--|-------------------------|
| product brand name | SETRON |
| product designation | 3LD Switch disconnecter |
| design of the product | Switch |
| display version / for switch position indicator manual operation | 1 ON - 0 OFF |
| design of the actuating element | Without handle |
| design of handle | without |
| type of the driving mechanism / motor drive | No |
| General technical data | |
| number of poles | 3 |
| number of poles / note | 3 |
| type of device | fixed mounting |
| type of switch | DIN-rail mounting |
| mechanical service life (switching cycles) / typical | 100 000 |
| electrical endurance (switching cycles) | |
| • at AC-23 A / at 690 V | 6 000 |
| I _{2t} value / with closed switch / at 690 V / for combination switch + gG fuse / maximum | 4 kA ² .s |
| let-through I _{2t} value / with closed switch / at 440 V / for combination switch + gG fuse / maximum | 4 kA ² .s |
| operating frequency / maximum | 50 1/h |
| Voltage | |
| insulation voltage / rated value | 690 V |
| surge voltage resistance / rated value | 6 kV |
| Protection class | |
| protection class IP | IP20 |
| protection class IP / on the front | IP20 |
| Dissipation | |
| power loss [W] | |
| • for rated value of the current / at AC / in hot operating state / per pole | 1.1 W |
| • per conductor / typical | 1 W |
| Current | |
| operational current | |
| • at 40 °C / rated value | 25 A |
| • at 45 °C / rated value | 25 A |
| • at 50 °C / rated value | 25 A |
| • at 55 °C / rated value | 25 A |
| • at AC / rated value | 25 A |

| | |
|---|--------------|
| <ul style="list-style-type: none"> • at AC-23 A / at 400 V / rated value | 20 A |
| <ul style="list-style-type: none"> • at AC-21 / at 690 V / rated value | 25 A |
| <ul style="list-style-type: none"> • at AC-21 A / at 240 V / rated value | 25 A |
| <ul style="list-style-type: none"> • at AC-21 A / at 440 V / rated value | 25 A |
| operational current / of upstream fuse / rated value | 25 A |
| let-through current / with closed switch | |
| <ul style="list-style-type: none"> • at 440 V / for combination switch + gG fuse / maximum | 3.5 kA |
| <ul style="list-style-type: none"> • at 690 V / for combination switch + gG fuse / maximum permissible | 4 kA |
| Main circuit | |
| operating power | |
| <ul style="list-style-type: none"> • at AC-23 A / at 240 V / rated value | 4 kW |
| <ul style="list-style-type: none"> • at AC-23 A / at 400 V / rated value | 10 kW |
| <ul style="list-style-type: none"> • at AC-23 A / at 440 V / rated value | 9 kW |
| <ul style="list-style-type: none"> • at AC-23 A / at 690 V / rated value | 9 kW |
| <ul style="list-style-type: none"> • at AC-3 / at 240 V / rated value | 4 kW |
| <ul style="list-style-type: none"> • at AC-3 / at 400 V / rated value | 8 kW |
| <ul style="list-style-type: none"> • at AC-3 / at 690 V / rated value | 7.5 kW |
| operational current / rated value | 25 A |
| Auxiliary circuit | |
| number of CO contacts / for auxiliary contacts | 0 |
| number of NC contacts / for auxiliary contacts | 0 |
| number of NO contacts / for auxiliary contacts | 0 |
| operating voltage / of auxiliary contacts / at AC / maximum | 500 V |
| continuous current / of the auxiliary contact / rated value | 10 A |
| insulation voltage / of the auxiliary switch / rated value | 500 V |
| Suitability | |
| suitability for use | |
| <ul style="list-style-type: none"> • main switch | Yes |
| <ul style="list-style-type: none"> • switch disconnecter | Yes |
| <ul style="list-style-type: none"> • EMERGENCY OFF switch | Yes |
| <ul style="list-style-type: none"> • safety switch | Yes |
| <ul style="list-style-type: none"> • maintenance/repair switch | Yes |
| Product details | |
| product feature | |
| <ul style="list-style-type: none"> • can be locked into OFF position | No |
| special product feature | Basic Switch |
| product extension / optional | |
| <ul style="list-style-type: none"> • motor drive | No |
| <ul style="list-style-type: none"> • voltage trigger | No |
| Short circuit | |
| conditional short-circuit current / with line-side fuse protection | |
| <ul style="list-style-type: none"> • at 440 V / by gG fuse / rated value | 10 kA |
| <ul style="list-style-type: none"> • at 690 V / by gG fuse / rated value | 6 kA |
| according UL | |
| operational current / at AC / according to UL 508/UL 60947-4-1 / rated value | 25 A |
| operating voltage / at AC / at 50/60 Hz / according to UL 508/UL 60947-4-1 / rated value | 600 V |
| active power [hp] / at AC / at 480 V / according to UL 508/UL 60947-4-1 / rated value | 10 |
| active power [hp] / at AC / at 600 V / according to UL 508/UL 60947-4-1 / rated value | 15 |
| short-time withstand current (SCCR) / at 600 V / according to UL 508/UL 60947-4-1 | 5 kA |
| continuous current / of upstream fuse / according to UL / rated value | 50 A |
| type of fuse / according to UL | RK5 |
| Number | |

| | |
|---|---|
| number of connectable NC contacts / for auxiliary contacts / attachable / maximum | 2 |
| number of connectable NO contacts / for auxiliary contacts / attachable / maximum | 4 |
| number of connectable CO contacts / for auxiliary contacts / attachable / maximum | 0 |

Connections

| | |
|---|--|
| AWG number / as coded connectable conductor cross section / solid | |
| <ul style="list-style-type: none"> • maximum • minimum | 6 14 |
| type of connectable conductor cross-sections / for copper conductor | |
| <ul style="list-style-type: none"> • solid • finely stranded / with core end processing • stranded | 1x (2.5 to 16 mm ²) 1x (2.5...16 mm ²) 1x (2.5 to 16 mm ²) |
| type of connectable conductor cross-sections / for auxiliary contacts | |
| <ul style="list-style-type: none"> • solid • finely stranded / with core end processing • stranded | 2x (0.75 ... 2.5 mm ²), 1x 4 mm ² 2x (0.75 ... 1.5 mm ²), 1x 2.5 mm ² 2x (0.75 ... 2.5 mm ²), 1x 4 mm ² |
| type of electrical connection | |
| <ul style="list-style-type: none"> • for main current circuit • for auxiliary contacts | box terminal Box terminals |

Requirements

| | |
|--|--------------------------------------|
| design of the fuse link | |
| <ul style="list-style-type: none"> • for short-circuit protection of the main circuit / required • for short-circuit protection of the auxiliary switch / required | fuse gL/gG: 25 A fuse gL/gG: 10 A |

Mechanical Design

| | |
|--|-------------------------------------|
| height | 60 mm |
| width | 36 mm |
| depth | 64 mm |
| fastening method | Built-in unit fixed-mounted version |
| fastening method | |
| <ul style="list-style-type: none"> • 4-hole front mounting • front mounting with central attachment • rail mounting | No No Yes |
| net weight | 200 g |

Environmental conditions

| | |
|--|-----------------|
| ambient temperature / during operation | |
| <ul style="list-style-type: none"> • minimum • maximum | -25 °C 55 °C |
| ambient temperature / during storage / minimum | -25 °C |

General Product Approval

Declaration of Conformity

[Confirmation](#)



other

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3LD3110-0TK05>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3LD3110-0TK05>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3LD3110-0TK05

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



