VIEW ON MATING SIDE



A = 32 CONTACTS L=4,5

Marking	Standard
Performance level	GI/O = Contact area level I / Termination tin
Flux proof	no
Fixing clip	no
Dimensions	SDA-85040-0002 sht.1
Technical Data	PS-85042-0001

A	GI/O	a1-16 b1-16
Contact symbol	Perform. level	Contact position number

ECN MG1998-2554 first release	REVISIONS	FOR PREVIOUS REVISIONS SEE MRI LIST
A	LTR	

UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ±2°

	INCH	METRIC
3 PLACE	± .	±
2 PLACE	± .	±
1 PLACE	± .	±

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DESIGN DIMENSION ☐ MM ☐ IN.

EQUIVALENT DIMENSION ☐ MM ☐ IN.

IF TWO DIMENSIONS ARE SHOWN THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY

DRWG BY	KN	SIGN
CHK'D BY	Ca	SIGN
APP'D BY	JB	SIGN
SCALE		

REVISE ONLY ON CAD SYSTEM | SH. | REV.

CADCAM PROJECT NAME s8504007 s11

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

TITLE 32 pos. female connector acc. DIN 41612 style B/2 contacts arrangement

molex MOLEX EUROPE

SHEET NO. 1 OF 1

DATE 97/07/30

PART NO. 85040-0713

DWG NO. SD-85040-0713

SIZE A