

## Specification Sheet

Part Number: 156-01547



Versatile design allows cable routing above, perpendicular or parallel to stud.

Can mount up to three bundles simultaneously, making efficient use of a single mounting point.

Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.

Article Number 156-01547

Type T50R0SBS5-6U-SET

Color Black (BK)

Quantity Per carton

Product Description Unique, two-piece design allows routing to be above, parallel or perpendicular to stud. This also enables up to three separate bundles to be fastened to the same stud. With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications. Available in standard and high-heat material options.

Short Description 2-Piece M5/T5/M6/T6 Stud Mount Tie, 8.0" Tie, 50lb Tensile Strength, PA66HS/PA66HIRHS, BK, 3000/pkg

Global Part Name T50R0SBS5-6U-SET-PA66HS/PA66HIRHS-BK

Minimum Tensile Strength (Imperial) 50.0

Minimum Tensile Strength (Metric) 222.0

Length L (Imperial) 8.0

Length L (Metric) 202.0

Fixation Method Stud Mount

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Width W (Imperial) 0.181

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.16

Bundle Diameter Min (Metric) 4.0

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 50.0

Cable Ties 156-01547

|                                     |  |
|-------------------------------------|--|
| Height H (Imperial)                 | 0.74   |
| Height H (Metric)                   | 18.75  |
| Mounting Hole Diameter D (Imperial) | 0.20" x 0.03"; 0.24" x 0.04"; 0.20   |
| Mounting Hole Diameter D (Metric)   | M5 x 0.8 T5 M6 x 1   |
| Stud Diameter (Metric)              | 6.0 mm 5.0 mm  |
| Stud Diameter (Imperial)            | 0.20 ", 0.24   |
| Material                            | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)<br>Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut                   | PA66HS PA66HIRHS   |
| Material Cable Tie                  | Polyamide 6.6 heat stabilized (PA66HS)   |
| UV Resistant (Yes/No)               | No   |
| Operating Temperature               | -40°F to +230°F (-40°C to +110°C)  |
| Reach Compliant (Article 33)        | Yes  |
| ROHS Compliant                      | Yes  |
| Package Quantity (Imperial)         | 3000   |

Package Quantity (Metric) 3000

Customs Number 3926909988

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)