

Han Shielded power module female



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 14 006 3121 |
| Specification | Han Shielded power module female |
| HARTING eCatalogue | https://b2b.harting.com/09140063121 |

Identification

| | |
|---------------------------|----------------------------|
| Category | Modules |
| Series | Han-Modular® |
| Type of module | Han® Shielded power module |
| Size of the module | Single module |
| Description of the module | With shielding plate |

Version

| | |
|---------------------------|---|
| Termination method | Crimp termination |
| Gender | Female |
| Shielding | Shielded |
| Number of contacts | 6 |
| Number of signal contacts | 2 |
| Number of power contacts | 4 |
| Details | Please order crimp contacts separately. 4x Han E® 2x Han D® |

Technical characteristics

| | |
|-------------------------|----------------------------|
| Conductor cross-section | 0.14 ... 4 mm ² |
| Rated current | 16 A |
| Rated voltage | 400 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 3 |



Pushing Performance
Since 1945

Technical characteristics

| | |
|--------------------------------|-------------------|
| Rated current (signal) | 10 A |
| Rated voltage (signal) | 400 V |
| Rated impulse voltage (signal) | 4 kV |
| Pollution degree (signal) | 3 |
| Insulation resistance | $>10^{10} \Omega$ |
| Limiting temperature | -40 ... +125 °C |
| Mating cycles | ≥ 500 |

Material properties

| | |
|---|------------------------------|
| Material (insert) | Polycarbonate (PC) |
| Colour (insert) | RAL 7032 (pebble grey) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Not contained |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R22 (HL 1-3) R23 (HL 1-3) |

Specifications and approvals

| | |
|----------------|--|
| Specifications | IEC 60664-1 IEC 61984 |
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| | |
|--------------------------------|---------------|
| Packaging size | 2 |
| Net weight | 14 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140185036 |



Pushing Performance
Since 1945

Commercial data

eCl@ss

27440217 Module for industrial connectors (power/signals)
