



MATERIAL NO.	ENG. NO.	LENGTH
1300640408	CC4030A57M080G	26.24' +12.50"-0 [8M +317MM-0]



FACE VIEW-FEMALE INSERT

FACE VIEW-MALE INSERT



- NOTES:
- 1) MATERIAL: SEE TABLE
  - 2) FINISHES: SEE TABLE
  - 3) LABEL IS MARKED WITH P/N, DATE CODE, VOLTAGE & AMPERAGE
  - 4) MATES WITH: QC 4 POLE CONNECTORS
  - 5) ELECTRICAL DATA:  
 10AWG UL TYPE: TC-ER/ST00W, STRANDED CABLE  
 POLES: 4  
 MAX VOLTAGE: 600V AC/DC  
 MAX THRU CURRENT: 32A  
 PROTECTION IP67  
 TEMPERATURE RANGE: -20°C TO 90°C
  - 6) PACKAGING:  
 CABLE ASSEMBLIES ARE BAGGED SEPERATLY IN POLY BAGS  
 WITH BAR CODE LABEL ATTACHED TO OUTSIDE OF BAG.
  - 7) ASSEMBLY IS RoHS COMPLIANT
  - 8) AGENCY CERTIFICATIONS:  
 UL LISTED PER UL 2237, E258922, CATEGORY PVVA

ITEM	QTY	DESCRIPTION	MATERIAL	FINISH
10	2	OVERMOLD	PVC	BLACK
9	1	LABEL	PLASTIC FILM	BLACK/YELLOW
8	2	WARNING LABEL	PLASTIC FILM	-----
7	4	QC SOCKET CONTACT	Cu ALLOY	GOLD PLATED
6	1	QC FEMALE INSERT	PVC	BLACK
5	1	QC FEMALE COUPLING NUT	ALUMINUM	CLEAR ANODIZE
4	4	QC PIN CONTACT	Cu ALLOY	GOLD PLATED
3	1	QC MALE INSERT	PVC	BLACK
2	1	QC MALE COUPLING NUT	ALUMINUM	CLEAR ANODIZE
1	1	10AWG 4 POLE CABLE	PVC	BLACK

UPDATED PROFILE  
 EC NO: JFG2014-1160  
 DRWNG:GUSTAFSON 2013/12/26  
 CHKD:VOU 2014/01/15  
 APPR:BMWOODMAN 2014/05/12

QUALITY SYMBOLS  
 ▽=0  
 ▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± .---	± .---
3 PLACES	± .---	± .005
2 PLACES	± 0.13	± .010
1 PLACE	± 0.25	± .020

ANGULAR ±1/2°

DRAFT WHERE APPLICABLE  
 MUST REMAIN  
 WITHIN DIMENSIONS

DIMENSION STYLE  
 IN/MM

DRAWN BY DATE  
 BRUPERT 2011/11/09

CHECKED BY DATE

APPROVED BY DATE  
 JFMURPHY 2012/04/17

MATERIAL NO.  
 SEE CHART

SCALE 1:1  
 DESIGN UNITS INCH  
 THIRD ANGLE PROJECTION

TITLE  
 QC FEMALE/MALE STR/STR  
 4 POLE EXTENSION

Molex MOLEX INCORPORATED

DOCUMENT NO. SD-130064-004  
 SHEET NO. 1 OF 1

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION