


| Date | SYM | REVISION RECORD | AUTH | DR. | CK. |
|----------|-----|---|------|------|-----|
| 11/26/05 | А | ADDED "ROHS COMPLIANT" | T.B. | B.S. | |
| 8/06/10 | В | REDRAWN IN AUTOCAD AND UPDATED SPECIFICATION | T.B. | B.S. | |
| 10/10/14 | С | UPDATED TO ROHS 2 COMPLIANT | T.B. | B.S. | |
| 06/16/17 | D | UPDATED MATERIAL SPECIFICATION | T.B. | B.S. | |
| | | | | | |



MATERIAL:

HOUSING: POLYPROPYLENE, BLACK

FLAMMABILITY RATING -UL94 HB, UL FILE NO. E216959

TEMPERATURE RANGE: -10°C to +100°C SPRINGS: SPRING STEEL, NICKEL PLATED

RIVETS: BRASS, NICKEL PLATED 9V SNAPS: BRASS, NICKEL PLATED

CONTACT RESISTANCE: UNDER $50m\Omega$ FOR +/- CONTACTS

PER EIA-540J000

ROHS 2 COMPLIANT

| Tolerance (Inches) | MPD Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735 | | | | | | |
|---------------------------|---|--------------------------|-------|------------------|--|--|--|
| Decimal | | | Scale | Drawn By B.S. | | | |
| ±.5 (.020) | | | | Approved By T.B. | | | |
| Fractional ± .8 (.030) | Title TEN "AA" CELL HOLDER WITH SNAP FASTENERS | | | | | | |
| Angular ± 3° | Date 06/16/17 | Drawing Number BH310AASF | | | | | |