



Product Description

High Performance Instrumentation, 1 Pair 16AWG (19x29) Tinned Copper, PVC Insulation E2 Color Code, Overall Beldfoil® Shield, PVC Outer Jacket, PLTC

Technical Specifications

Product Overview

Suitable Applications: Instrumentation, Sensors, Valves, Positioners, 4-20mA, 0-10V										
Constr	ruction Details	5								
Conducto	-									
	t No. of Elements		Stranding	Material						
Pair(s)	1	16 AWG	i 19x29	TC - Tinned Copper						
nsulatio	n									
Element Material Nom. Thickness Nom. Insulation Diameter Color Code										
Pair(s)	PVC - Polyvinyl C	Chloride C).019 in (0.48 r	nm) 0.096 in (2.4 m	nm)	Black, Red				
Outer Shield										
Shield Type Material Coverage Drainwire Type										
Tape	Bi-Laminate (Alum+Pol	ly) 100%	18 AWG (19x30) 1	°C					
Outer Ja	-k-4									
		Nom. Thic	knoon No	m. Diameter Ripo	ord					
				D in (6.86 mm) Yes	Joru					
	Cable Diameter (No		· · · ·	. ,						
Overall		minar). 0.	.270 11 (0.00 11							
Electri	cal Characteri	stics								
Electrica	ls									
Element	t Nom. Conductor	DCR N	om. Capacitar	nce Cond-to-Cond	Nom. Capa	citance Cond-	-to-Other (Conds	+ Shield)	Max. Current	
Pair(s)	4.5 Ohm/1000ft	68	68 pF/ft (220 pF/m)		121 pF/ft (397 pF/m)			6.2 Amps per conductor at 2	5°C	
/oltage										
-	age Rating									
	PLTC, CMG)									
Mechanical Characteristics										
Tempera	ture									
UL Tem	perature Opera	ating								
105°C	-30°C to	+105°C								
Table No	otes:	A	WM 80°C							
Bend Rad	dius									
Ctations										

Stationary Min.	Installation Min.		
2.6 in (66 mm)	2.6 in (66 mm)		

Max. Pull Tension:	105 lbs (47.6 kg)
Bulk Cable Weight:	41 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Sunlight Resistance
Flammability / Reaction to Fire:	UL 1685 UL Loading, FT4, T-29-520, IEEE 1202
NEC / UL Compliance:	Article 725, Article 727, Article 800, CMG, ITC, PLTC
AWM Compliance:	AWM 2464
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:

Revision Number: 0.540 Revision Date: 04-14-2023

Part Numbers

Variants

ltem #	Color	Putup Type	Length	UPC	Footnote
9316 060U500	Chrome	UnReel	500 ft	612825228356	
9316 0601000	Chrome	Reel	1,000 ft	612825228363	
9316 060U1000	Chrome	UnReel	1,000 ft	612825228349	
9316 0605000	Chrome	Reel	5,000 ft	612825228387	Z
9316 06010000	Chrome	Reel	10,000 ft	612825228370	СZ

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.