

CMOS Logic

- ◆ CMOS 2-Input NOR Gate
- ◆ High Speed Operation : $t_{pd} = 2.65\text{ns}$ (TYP.)
- ◆ Operating Voltage Range : $2V \sim 5.5V$
- ◆ Low Power Consumption : $1\mu A$ (MAX.)

■ APPLICATIONS

- Palmtops
- Digital equipment

■ GENERAL DESCRIPTION

The XC74UL02AA is a 2-input CMOS NOR Gate, manufactured using silicon gate CMOS fabrication.

CMOS low power circuit operation makes high speed LS-TTL operation achievable.

With a wave forming buffer connected internally, stabilized output can be achieved as the circuit offers high noise immunity. As the XC74UL02AA is integrated into mini molded, SSOT-25 and SOT-25 packages, high density mounting is possible.

■ FEATURES


High Speed Operation : $t_{pd} = 2.65\text{ns}$ (TYP.)

Operating Voltage Range : $2V \sim 5.5V$

Low Power Consumption : $1\mu A$ (MAX.)

Ultra Small Packages : SSOT-25 and SOT-25

■ PIN CONFIGURATION



■ FUNCTIONS

INPUT		OUTPUT
A	B	Y
L	L	H
L	H	L
H	L	L
H	H	L

H=High level

L=Low level

■ ABSOLUTE MAXIMUM RATINGS

T_a=-40°C~85°C

PARAMETER	SYMBOL	RATINGS	UNITS
Supply Voltage	V _{CC}	-0.5~+6.0	V
Input Voltage	V _{IN}	-0.5~+6.0	V
Output Voltage	V _{OUT}	-0.5~V _{CC} +0.5	V
Input Diode Current	I _{IK}	-20	mA
Output Diode Current	I _{OK}	± 20	mA
Output Current	I _{OUT}	± 25	mA
V _{CC} ,GND Current	I _{CC} ,I _{GND}	± 50	mA
Power Dissipation(T _a =55°C)	P _d	150	mW
Storage Temperature Range	T _{STG}	-65~+150	°C

* Voltage is all ground standardized.

XC74UL02AA

■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	Vcc(V)	CONDITIONS	UNITS
Supply Voltage	Vcc	-	2~5.5	V
Input Voltage	V _{IN}	-	0~5.5	V
Output Voltage	V _{OUT}	-	0~Vcc	V
Operating Temperature Range	T _{opr}	-	-40~+85	°C
Output Current	I _{OH}	3.0	-4	mA
		4.5	-8	
	I _{OL}	3.0	4	
		4.5	8	
Input Rise and Fall Time	t _{r,tf}	3.3	0~100	ns
		5.0	0~20	

■ DC ELECTRICAL CHARACTERISTICS


PARAMETER	SYMBOL	CONDITIONS			Ta=25°C			Ta=-40°C~85°C		UNITS
					MIN.	TYP.	MAX.	MIN.	MAX.	
Input Voltage	V _{IH}	2.0			1.5	-	-	1.5	-	V
		3.0			2.1	-	-	2.1	-	
		5.5			3.85	-	-	3.85	-	
	V _{IL}	2.0			-	-	0.5	-	0.5	V
		3.0			-	-	0.9	-	0.9	
		5.5			-	-	1.65	-	1.65	
Output Voltage	V _{OH}	2.0	V _{IN} =V _{IH}	I _{OH} =-50μA	1.9	2.0	-	1.9	-	V
		3.0			2.9	3.0	-	2.9	-	
		4.5			4.4	4.5	-	4.4	-	
		3.0		I _{OH} =-4mA	2.58	-	-	2.48	-	
		4.5		I _{OH} =-8mA	3.94	-	-	3.80	-	
	V _{OL}	2.0	V _{IN} =V _{IL}	I _{OL} =50μA	-	-	0.1	-	0.1	V
		3.0			-	-	0.1	-	0.1	
		4.5			-	-	0.1	-	0.1	
		3.0		I _{OL} =4mA	-	-	0.36	-	0.44	
		4.5		I _{OL} =8mA	-	-	0.36	-	0.44	
Input Current	I _{IN}	0~5.5	V _{IN} =V _{CC} or GND	-	-0.1	-	0.1	-1.0	1.0	μ A
Static Supply Current	I _{CC}	5.5	V _{IN} =V _{CC} or GND, I _{OUT} =0μA	-	-	1.0	-	10.0		

■ SWITCHING ELECTRICAL CHARACTERISTICS

tr=tf=3ns

PARAMETER	SYMBOL	CONDITIONS			Ta=25°C			Ta=-40°C~85°C		UNITS
					MIN.	TYP.	MAX.	MIN.	MAX.	
Delay Time	t _{PLH}	15pF	3.3		-	3.9	7.9	1.0	9.5	ns
			5.0		-	2.7	5.5	1.0	6.5	
		50pF	3.3		-	5.5	11.4	1.0	13.0	ns
			5.0		-	3.9	7.5	1.0	8.5	
	t _{PHL}	15pF	3.3		-	3.5	7.9	1.0	9.5	ns
			5.0		-	2.6	5.5	1.0	6.5	
		50pF	3.3		-	4.9	11.4	1.0	13.0	ns
			5.0		-	3.6	7.5	1.0	8.5	
Input Capacitance	C _{IN}	-	5.0	V _{IN} =V _{CC} or GND	-	4	10	-	10	pF
Power Dissipation Capacitance	C _{PD}	No Load, f=1MHz			-	9.7	-	-	-	pF

■ WAVEFORM



■ TEST CIRCUIT

