

PACT MCR-V2-4012-70-250-1A-1 - Current transformer



2905882

<https://www.phoenixcontact.com/us/products/2905882>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Window-type current transformer, 250 A AC primary current; 1 A AC secondary current; accuracy class 1; 5 VA rated power

Commercial data

Item number	2905882
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	C444
Product key	CK4A11
GTIN	4055626004822
Weight per piece (including packing)	317.6 g
Weight per piece (excluding packing)	250 g
Customs tariff number	85043129
Country of origin	DE

PACT MCR-V2-4012-70-250-1A-1 - Current transformer



2905882

<https://www.phoenixcontact.com/us/products/2905882>

Technical data

Product properties

Product type	Current transformer
--------------	---------------------

Electrical properties

Rated insulation voltage	1 kV (Phase/neutral conductor)
--------------------------	--------------------------------

General

Can be calibrated	no
Converter type	Window-type current transformer

Input data

Current transformers

Rated power	5 VA
Thermal rated short-time current	$I_{th} = 60 * I_n$
Thermal rated continuous current	$I_d = 1.2 * I_n$
Rated surge current	$I_{dyn} = 2.5 * I_{th}$
Rated frequency f_n	50 Hz 60 Hz
Primary rated current I_{pn}	0 A AC ... 250 A AC
Primary rated current range	1 A AC ... 4000 A AC (depends on type)
Can be calibrated	no
Converter type	Window-type current transformer

Output data

Signal

Designation	Current output
Secondary rated current I_{sn}	1 A AC
Surge current limitation factor	FS 5
Accuracy class	1

Connection data

Connection method	Screw connection
Conductor cross section flexible	2x 2.5 mm ² ... 4 mm ² (Secondary terminals)

Dimensions

Item dimensions

Width	30 mm
Height	90 mm
Depth	70 mm

Item dimensions with alternative mounting

PACT MCR-V2-4012-70-250-1A-1 - Current transformer



2905882

<https://www.phoenixcontact.com/us/products/2905882>

Width	70 mm
Height	90 mm
Depth	30 mm

Copper rail

Width	40 mm
Height	12 mm

Copper rail 2

Width	30 mm
Height	10 mm

Circular conductor

Diameter	33 mm
----------	-------

Material specifications

Housing material	PA 6.6
------------------	--------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-25 °C ... 40 °C
Ambient temperature (storage/transport)	-25 °C ... 40 °C
Permissible humidity (operation)	Use only indoors, non-condensing

Approvals

CE

Certificate	CE-compliant
-------------	--------------

UKCA

Certificate	UKCA-compliant
-------------	----------------

Standards and regulations

Standards/regulations	EN 61869
-----------------------	----------


PACT MCR-V2-4012-70-250-1A-1 - Current transformer



2905882

<https://www.phoenixcontact.com/us/products/2905882>

Drawings



PACT MCR-V2-4012-70-250-1A-1 - Current transformer



2905882

<https://www.phoenixcontact.com/us/products/2905882>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2905882>



EAC

Approval ID: RU*DE*08.B.01187/19

PACT MCR-V2-4012-70-250-1A-1 - Current transformer



2905882

<https://www.phoenixcontact.com/us/products/2905882>

Classifications

ECLASS

ECLASS-11.0	27210902
ECLASS-13.0	27210902
ECLASS-12.0	27210902

ETIM

ETIM 8.0	EC002048
----------	----------

UNSPSC

UNSPSC 21.0	39121000
-------------	----------

PACT MCR-V2-4012-70-250-1A-1 - Current transformer



2905882

<https://www.phoenixcontact.com/us/products/2905882>

Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"
------------	--

PACT MCR-V2-4012-70-250-1A-1 - Current transformer



2905882

<https://www.phoenixcontact.com/us/products/2905882>

Accessories

PACT-FAST-MNT-W13-L65 - Mounting material

2276625

<https://www.phoenixcontact.com/us/products/2276625>



The transformer quick-action mechanism enables the lightning-fast mounting of PACT current transformers on the power rail. The installation can be completed easily by hand without the use of tools. Fixing pins: 65 mm, holding latches: 13 mm

PACT-FAST-MNT-W13-L40 - Mounting material

2276612

<https://www.phoenixcontact.com/us/products/2276612>



The transformer quick-action mechanism enables the lightning-fast mounting of PACT current transformers on the power rail. The installation can be completed easily by hand without the use of tools. Fixing pins: 40 mm, holding latches: 13 mm

PACT MCR-V2-4012-70-250-1A-1 - Current transformer



2905882

<https://www.phoenixcontact.com/us/products/2905882>

PACT MCR-RA - DIN rail adapter

2277598

<https://www.phoenixcontact.com/us/products/2277598>

Adapter for mounting on DIN rails.



Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com