

PRO-SHIELD® 7002

ONE COMPONENT CORROSION RESISTANT
ELECTRICALLY CONDUCTIVE SILICONE
SEALANT



Customer Value Proposition:

Parker Chomerics PRO-SHIELD® 7002 is a nickel plated graphite filled electrically conductive silicone sealant.

It is an easy to use electrically conductive sealant or gap filler for use on horizontal or vertical surfaces. PRO-SHIELD 7002 flows smoothly for application on parts with complex geometries and difficult to fill crevasses.

PRO-SHIELD 7002 is a cost-effective solution for reducing electromagnetic interference (EMI) in commercial electronics.

Contact Information:

Parker Hannifin Corporation
Chomerics Division
77 Dragon Ct.
Woburn, MA 01801 USA

phone 781 935 4850
fax 781 933 4318
CHomailbox@parker.com

www.parker.com/chomerics




Product Features:

- Easy to use
- One component – no mixing or weighting required
- Moisture cure silicone – tack free in 24hrs, reaches full cure in 7 days
- Volume resistivity: < 0.8 ohm-cm.
- Shielding effectiveness: 40-60 dB
- Lap shear: 125 PSI

Typical Applications:

- Electronic assemblies
- Medical devices
- Industrial cabinets
- Access panels
- Engine Control Modules (ECMs)
- Telecom Infrastructure
- Portable electronics
- Commercial aircraft

 **WARNING:** This product can expose you to **TITANIUM DIOXIDE, NICKEL, and FORMALDEHYDE** which are known to the State of California to cause cancer, and **METHANOL** which is known to the State of California to cause birth defects and/or other reproductive harm. For more information go to www.P65Warnings.ca.gov

CHOMERICS and PRO-SHIELD is a registered trademark of Parker Hannifin Corporation. © 2018

PRO-SHIELD 7002



ENGINEERING YOUR SUCCESS.

Product Information


PRO-SHIELD 7002 ELECTRICALLY CONDUCTIVE SEALANT

PRO-SHIELD 7002		
Typical Properties	Typical Values	Test Method
Packaging	30cc syringe, 6oz EFD tube	N/A
Primer Included	No	N/A
Polymer Family	Silicone	N/A
Filler Material	Nickel-Plated Graphite	N/A
Color	Gray	N/A
Volume Resistivity	0.800 ohm-cm	CHO-95-40-5555* (Q/C)
Shielding Effectiveness (dB) Avg.	40-60 dB	CHO-TM-TP11
Calculated VOC (g/L)	0	Calculated
Specific Gravity	2.2	ASTM D792
Shelf life, date of manufacture (months)	9	N/A

Ordering Information

Part Number	Packaging	Weight (grams)
90-05-7002-0000	30cc syringe	54
90-01-7002-0000	6oz EFD tube	275

Primer not included. For best adhesion, Chomerics recommends applying PRO-SHIELD 7201 primer to a cleaned and degreased substrate before applying PRO-SHIELD 7002.

 WARNING: This product can expose you to TITANIUM DIOXIDE, NICKEL, and FORMALDEHYDE which are known to the State of California to cause cancer, and METHANOL which is known to the State of California to cause birth defects and/or other reproductive harm. For more information go to www.P65Warnings.ca.gov

CHOMERICS and PRO-SHIELD is a registered trademark of Parker Hannifin Corporation. © 2018

PRO-SHIELD 7002



ENGINEERING YOUR SUCCESS.