View on mating side

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
c	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
b																
a	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A

A = 32 standard contacts L=2

Marking	Standard
Performance level	G2/0 = Contact area perform. level 2 / Termination tin
Flux proof	no
Fixing clip	no
Dimensions	609-6043-201 sht.1
Technical Data	PS-85013-0002

A	G2/0	a1-16 c1-16
Contact symbol	Perform. level	Contact position number

REVISE ONLY ON CAD SYSTEM | SH. | REV.

LTR	REVISIONS	FOR PREVIOUS REVISIONS SEE MR1 LIST
A	first release ECN No. MG1999-0303	

UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ±2°

	INCH	METRIC
3 PLACE	± .	±
2 PLACE	± .	±
1 PLACE	± .	±

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DESIGN DIMENSION ☒ MM ☐ IN.

EQUIVALENT DIMENSION ☐ MM ☐ IN.

IF TWO DIMENSIONS ARE SHOWN THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY

DRWG BY	Ca	SIGN
CHK'D BY	Er	SIGN
APP'D BY	FB	SIGN
SCALE		

CADCAM PROJECT NAME

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

TITLE

48 pos. Male connector acc. DIN 41612 style R/2 contacts arrangement

MOLEX EUROPE

SHEET NO. 1 OF 1

DATE 99/05/27

PART NO. 85013-0062

DWG NO. SDA-85013-0062

SIZE A