

External 240V Tower Battery Pack for Select UPS Systems (BP240V400C)

MODEL NUMBER: **BP240V400C**



Highlights

- Extends runtime of compatible UPS Systems using 240VDC configuration
- Includes built in 7A charger
- Internal DC disconnect
- 10 year design lifespan
- Hardwire installation
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Description

The BP240V400C External Battery Pack with built-in 7A charger offers extended battery runtime when used in conjunction with compatible UPS systems. Requires BP240EXTNDR15A to connect to UPS. Cabling for additional BP240V400C battery packs is contractor supplied.

COMPATIBLE UPS SYSTEMS: SU20K3/3, SU30K3/3 and other UPS systems specifying the use of this battery pack

Features

- Offers extended-run UPS operation when used in conjunction with compatible UPS systems
- Multiple battery packs can be daisy-chained through each other to the UPS for even longer extended run operation
- Includes built-in 7A charger powered via hardwire 120VAC 30A input connection
- Internal DC disconnect
- 10 year design lifespan

Specifications

OVERVIEW	
UPC Code	037332185037
INPUT	
Input Phase	3-Phase
BATTERY	
Expandable Runtime	Yes
DC System Voltage (VDC)	240

UPS Connection	Requires BP240EXTNDR15A to connect to UPS
PHYSICAL	
Material of Construction	Steel
External Battery Pack Form Factor	Tower
Form Factors Supported	Tower
Installation Form Factors Supported with Included Accessories	Tower
Shipping Dimensions (hwd / in.)	66.00 x 46.00 x 48.00
Shipping Dimensions (hwd / cm)	167.64 x 116.84 x 121.92
Shipping Weight (lbs.)	2200.00
Shipping Weight (kg)	997.90
Unit Dimensions (hwd / in.)	59.000 x 29.000 x 31.500
Unit Dimensions (hwd / cm)	149.9 x 73.7 x 80
Unit Weight (lbs.)	2090
Unit Weight (kg)	948.01
Unit Weight Details	Floor loading of 297 lbs per sq. ft. / 1452 kg per sq. meter
STANDARDS & COMPLIANCE	
Product Compliance	UKCA; Trade Agreements Act (TAA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	1-year limited warranty