# NSYS3DB6415

Spacial S3DB H600xW400xD150. IP66, IK10, RAL7035. No





#### Main

Range	Spacial
Product name	Spacial S3DB
Application	Terminal application
Category	Compact enclosure
Enclosure nominal height	23.62 in (600 mm)
Enclosure nominal width	15.75 in (400 mm)
Enclosure nominal depth	5.91 in (150 mm)
Door type	Solid
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Installation accessory type	Horizontal or vertical position Wall-mounting
Product destination	For equipping with terminal
Device composition	1 body

### Complementary

Body type	Single piece body Gutter-shaped front rail double sheet thickness
Number of doors	Front face 1
Door opening side	Reversible 180 °)
Lock type	3 points lock, 3 mm double-bar
Accessibility for operation	Front
Removable parts	Door by hinges
Material	steel
Surface finish	Epoxy-polyester powder
Color	Gray RAL 7035)
Standards	IEC 62208
Product Certifications	LR UL BV DNV CUL GL
Net Weight	19.70 lb(US) (8.936 kg)

#### Environment

IK degree of protection	IK10 IEC 62262
IP degree of protection	IP66 IEC 60529

# Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480158728
Nbr. of units in pkg.	1
Package weight(Lbs)	19.70 lb(US) (8.936 kg)
Returnability	No
Country of origin	FR

# Packing Units

Unit Type of Package 1	PCE
Package 1 Height	24.02 in (61 cm)
Package 1 width	16.34 in (41.5 cm)
Package 1 Length	7.87 in (20 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <sup>™</sup> EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

### Contractual warranty

Warranty	18 months	