



REVISIONS			
LTR	DESCRIPTION	DATE	APPROVED



NOTES: CONFORMS TO MIL-C-39012 SMA SERIES

MATERIAL:

1. BODY = STAINLESS STEEL TYPE 303, COND. A PER ASTM A582.
2. CONTACT = BERYLLIUM COPPER PER ASTM B196.
3. INSULATOR = TEFLON TFE PER ASTM D1710.

FINISHES:

1. BODY = GOLD PLATE PER MIL-G-45204 TYPE II, CLASS 0, GRADE C OVER STRESS FREE NICKEL PER QQ-N-290.
2. CONTACT = GOLD PLATE PER MIL-G-45204 TYPE II, CLASS I, GRADE C OVER STRESS FREE NICKEL PER QQ-N-290.

PROPRIETARY INFORMATION
NOT TO BE RELEASED
WITHOUT WRITTEN PERMISSION
FROM AN AUTHORIZED
REPRESENTATIVE OF
APPLIED ENGINEERING PRODUCTS.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON FRAC. 1/64 DECIMAL ANGLES ± 2°			DRAWN DATE D.N. 5-28-96		APPLIED ENGINEERING PRODUCTS 104 John W. Murphy Drive, P.O. Box 510 New Haven, CT 06513		
			CHECKED DATE YPS 5-29-96				
MATERIAL: SEE NOTES			APPROVED DATE [Signature] 5/29/96		SMA PRINTED CIRCUIT MOUNT JACK		
			FINISH: SEE NOTES				
SEE NOTES			SIZE A	CODE IDENT NO. 19505	9650-1113-050		
			SCALE 5:1			SHEET 1 OF 1	