

# BL2 BPC 1541E-8/0 - Box PC



1272829

<https://www.phoenixcontact.com/us/products/1272829>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

IP30-rated fanless industrial box PC (BPC) with energy-efficient Intel® Atom® E3940 processor



## Commercial data

Item number	1272829
Packing unit	1 pc
Sales key	DR12
Product key	DRBABA
GTIN	4063151465032
Weight per piece (including packing)	934 g
Weight per piece (excluding packing)	762 g
Customs tariff number	84715000
Country of origin	TW

## Technical data

### Product properties

Product type	Box PC
--------------	--------

### Computer data

Processor	Intel® Atom™ E3940 1.6 GHz
Operating system	without operating system
Cooling	passive
RAM	8 GB LPDDR4

### Display

Display type	none
--------------	------

### System properties

User software	without user software
---------------	-----------------------

### Electrical properties

Maximum power dissipation for nominal condition	16.8 W
---	--------

### Supply

Supply voltage (DC)	24 V DC (CE rating)
Supply voltage range	12 V DC ... 30 V DC (Labeled operational voltage is 12 ... 30 V DC)
Max. current consumption	0.7 A (24 V DC)
Typical current consumption	0.53 A (24 V DC)

### Connection data

#### Screw connection

Connection method	Screw connection
Conductor cross section, rigid	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section, flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	25 ... 14

### Interfaces

Interfaces	1x DP++
	2x USB 3.0
	2x COM ports
Network	2x Ethernet (10/100/1000 Mbps), RJ45
LAN chipset	Intel® I210-AT

### Dimensions

#### External dimensions

Width / Height / Depth	99 mm / 92 mm / 63 mm
------------------------	-----------------------

1272829

<https://www.phoenixcontact.com/us/products/1272829>

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP30
Ambient temperature (operation)	-20 °C ... 60 °C (with 0.5 m/s airflow)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 85 % (non-condensing)
Shock	15g, 11 ms in accordance with IEC 60068-2-27
Vibration (operation)	1g, according to EN 60068-2-6

## Approvals

### Conformity/Approvals

Conformance	CE-compliant
FCC	Title 47 Part 15 Subpart B:2018 Class A

## Mounting

Mounting type	DIN rail mounting
	Wall mounting (Accessories required)

# BL2 BPC 1541E-8/0 - Box PC



1272829

<https://www.phoenixcontact.com/us/products/1272829>

## Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1272829>



**EAC**

Approval ID: RU C-DE.A\*08.B01708



**EAC-RoHS**

Approval ID: RU\*-DE\*HB.B.00386/20

# BL2 BPC 1541E-8/0 - Box PC



1272829

<https://www.phoenixcontact.com/us/products/1272829>

## Classifications

### ECLASS

ECLASS-11.0	19200102
ECLASS-12.0	19200102
ECLASS-13.0	19200102

### ETIM

ETIM 8.0	EC001413
----------	----------

### UNSPSC

UNSPSC 21.0	43211500
-------------	----------

# BL2 BPC 1541E-8/0 - Box PC

1272829

<https://www.phoenixcontact.com/us/products/1272829>



## Environmental product compliance

REACH SVHC

Lead 7439-92-1

# BL2 BPC 1541E-8/0 - Box PC



1272829

<https://www.phoenixcontact.com/us/products/1272829>

## Accessories

### SI-RND-U1A - Data interface

1425185

<https://www.phoenixcontact.com/us/products/1425185>

Service socket with USB A 3.0 (socket/socket), with protective cover



---

### DP TO VGA ADPTR - Adapter

2400173

<https://www.phoenixcontact.com/us/products/2400173>

DisplayPort to VGA video adapter



# BL2 BPC 1541E-8/0 - Box PC

1272829

<https://www.phoenixcontact.com/us/products/1272829>



## DP TO DVI ADPTR - Adapter

2400174

<https://www.phoenixcontact.com/us/products/2400174>

DisplayPort to DVI-i video adapter



---

## VL 2.0M DP CABLE - Connecting cable

2404774

<https://www.phoenixcontact.com/us/products/2404774>

DisplayPort (DP) cable (2 m) for use with industrial computers





## BL2 BPC 1541E-8/0 - Box PC

1272829

<https://www.phoenixcontact.com/us/products/1272829>



## BL2 BPC 1500 WALL MOUNT KIT - Mounting kit

1147655

<https://www.phoenixcontact.com/us/products/1147655>

Mounting kit



---

## BL2 BPC 1500 RTC BATTERY - Battery/accumulator

1147739

<https://www.phoenixcontact.com/us/products/1147739>

Replacement battery (BR2030) for BL2 BPC 1500... IPCs



## BL2 BPC 1541E-8/0 - Box PC

1272829

<https://www.phoenixcontact.com/us/products/1272829>



## BL2 BPC 1500 DIN RAIL KIT - Mounting kit

1147464

<https://www.phoenixcontact.com/us/products/1147464>



DIN rail mounting kit for BL2 BPC 15... products

---

## BL2 BPC 1500 64GB M.2 SSD KIT - Memory

1147738

<https://www.phoenixcontact.com/us/products/1147738>



64 GB M.2 SSD kit for BL2 1500 IPC, heat spreader, bracket, and thermal pads are included

# BL2 BPC 1541E-8/0 - Box PC

1272829

<https://www.phoenixcontact.com/us/products/1272829>



## BL2 BPC 1500 128GB M.2 SSD KIT - Memory

1147737

<https://www.phoenixcontact.com/us/products/1147737>

128 GB M.2 SSD kit for BL2 1500 IPC, heat spreader, bracket, and thermal pads are included



## MC 1,5/ 2-STF-3,5 - PCB connector

1847055

<https://www.phoenixcontact.com/us/products/1847055>

PCB connector, nominal cross section: 1.5 mm<sup>2</sup>, color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Tin, contact connection type: Socket, number of potentials: 2, number of rows: 1, number of positions: 2, number of connections: 2, product range: MC 1,5/...-STF, pitch: 3.5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, plug-in system: COMBICON MC 1,5, locking: Screw locking mechanism, mounting: Screw flange, type of packaging: packed in cardboard



Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)