



Product: 6403UE ☑

Security & Sound, #20-5c, BC, CMP

Product Description

Security & Sound Cable, Plenum-CMP 5-20 AWG stranded bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

Technical Specifications

Suitable Applications:			Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls					
Construction Details								
Conductor								
Element	No. of Elements	Size	Stranding		Material			
Conductor(s)	5	20 AW	G 7x28	вс	- Bare Copper			
nsulation								
Element	Material		Nom. Thickno	ess	Nom. Insulat	on Diameter	Color Code	
Conductor(s)	PVC - Polyvinyl Chloride		0.009 in (0.23	mm)	0.054 in (1.4 r	nm)	Black, Red, White, Green, Brown	



Outer Jacket

Material	Nom. Thickness	Nom. Diameter	Ripcord	
PVC - Polyvinyl Chloride	0.015 in (0.38 mm)	0.176 in	Yes	
Overall Cable Diameter (Nominal): 0.176 in				

Electrical Characteristics

Electricals

Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current	
10.71 Ohm/1000ft	27 pF/ft (89 pF/m)	3 Amps per Conductor at 25°C	

Voltage

UL Voltage Rating

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	0°C To +75°C

Bend Radius

Stationary Min.	Installation Min.
1.76 in (44.7 mm)	1.76 in

Max. Pull Tension:	63 lbs (29 kg)
Bulk Cable Weight:	26.5 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	NFPA 262 (UL910), FT6, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	5403UE

History

Update and Revision:	Revision Number: 0.300 Revision Date: 05-05-2023	

Part Numbers

Variants

Item #	Color	UPC	Footnote
6403UE 8771000	Natural	612825176817	С

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.