

TCXO


RTX-2016AF333-S-48.000-TR

Page 1 of 3

ELECTRICAL SPECIFICATION

PARAMETER	SYMBOL	CONDITIONS	VALUE	UNIT
Nominal Frequency	fo	Vcc ±5%	48.000	MHz
Supply Voltage, nom.	V _{cc}	Vcc ±5%	3.3	VDC
Supply Current, max	Is	Vcc ±5%	2.5	mA
Operating Temperature Range	Та		-30 ~ +85	°C
Storage Temperature Range	T(stg)	Absolute max	-40 ~ +85	°C
Frequency Stability vs. Temperature	∆f/fo(Ta)	Reference to +25°±2°C (-30 ~ +85°C)	±0.5	ppm
Frequency Stability				
vs. Supply Voltage	$\Delta f/f_{V}$	Vcc ±5%	±0.2	ppm
vs. Load	$\Delta f/f_L$	Load ±10%	±0.2	ppm
vs. Aging max	∆f/fo(year)	Per Year at +25°C ± 2°C	±1.0	ppm
Initial Frequency Calibration, max		Measured at 25°C, after 2 reflows	±2.0	ppm
Output Level, Clipped Sine Wave		10kΩ // 10 pF ±10%	0.8	V_{P-P}

■ MECHANICAL SPECIFICATION






RTX-2016AF333-S-48.000-TR

Page 2 of 3

REFLOW PROFILE



	Reflow profile	
Temperature Min Preheat	T _{SMIN}	150°C
Temperature Max Preheat	T _{SMAX}	200°C
Time (T _{SMIN} to T _{SMAX})	t _s	60-120 sec.
Temperature	T_L	217°C
Peak Temperature	T_P	260°C
Ramp-up rate	R _{UP}	3°C/sec max.
Ramp-down rate	R _{DOWN}	6°C/sec max.
Time within 5°C of Peak Temperature	t _P	30 sec.
Time t[25°C] to Peak Temperature	t[25°C] to Peak	480 sec.
Time	t _L	60-150 sec.

ENVIRONMENTAL

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
REACH	Compliant
RoHS	Compliant
TERMINATION FINISH	Au





TCXO

RTX-2016AF333-S-48.000-TR

Page 3 of 3

MARKING

Rx48.00 • AF3yw

x – Internal Production ID code

y – Year code

w - Week code

YEAR CODE		
Code		
5		
6		
7		
8		
9		
0		
1		
2		
3		

ALPHA WEEK CODE TABLE					
Week	Code	Week	Code	Week	Code
1	а	19	S	37	K
2	b	20	t	38	L
3	С	21	u	39	М
4	d	22	V	40	N
5	е	23	W	41	0
6	f	24	Х	42	Р
7	g	25	У	43	Q
8	h	26	Z	44	R
9	i	27	Α	45	S
10	j	28	В	46	Т
11	k	29	С	47	U
12	I	30	D	48	V
13	m	31	Е	49	W
14	n	32	F	50	Х
15	0	33	G	51	Υ
16	р	34	Н	52	Z
17	q	35	I		
18	r	36	J		

APPROVALS

RALTRON		
Created by, date:	AR, January 28, 2019	
Eng. approval, date: CP, January 28, 2019		
Revision: A		

Raltron Electronics / RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that he information is accurate, reliable or current. The product information is provided only for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright @ 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.