



#### **Product Description**

DIN 1.0/2.3 75 Ohm Adapters are available in DIN-DIN, DIN-BNC, and DIN-N connector interface configurations. Adapters can be used for discrete cable-to-cable connections or installed onto break-out panel assemblies for high-density applications.



 Isolated DIN-DIN and DIN-BNC Panel Mount Adapters "isolate" transmission line ground signal from external noise conducted on breakout panels or adjacent connectors.



 Inline Adapters are available in a variety of DIN-BNC interface options and can be used to connect installed BNC cables to new DIN-based Broadcast equipment or our new high-density Miniature-Size DIN Video Jackfields



• DIN 1.0/2.3 Adapters are made with precision machined components designed to provide long-term durability, reliability, and performance.



# **Specifications**

### Electrical

Impedance: 75 Ohms

Frequency Range: Specified on Individual

Sales Drawing

Return Loss: Specified on Individual

Sales Drawing

#### Mechanical

Durability: 500 Cycles Minimum

#### Material

Body: Brass

Center Contacts: Beryllium Copper N Male Pin: Brass

Insulators: Teflon®

#### **Finishes**

Body: Gold: Gold over Nickel

Nickel: Nickel over Copper

Outer/Center Contacts: Gold over Nickel

This series complies with CECC 22230 specifications.

















Photo 1

Photo 2

Photo 3 Photo 4

Photo 5

Photo 6

Photo 7

Photo 8

## Part Numbers

KINGS® Part Number	Description	Packaging	Photo
034G-034-00002H	DIN-Jack/DIN-Jack Bulkhead Isolated, Gold	Single	1
034G-034-00003H	DIN-Jack/DIN-Jack Inline, Gold	Single	2
206G-034-00001N	DIN-Jack/BNC-Jack Inline, Nickel	Single	3
206G-034-00002N	DIN-Plug/BNC-Jack Inline, Nickel	Single	4
206G-034-00003N	DIN-Jack/BNC-Jack Bulkhead Isolated, Nickel	Single	5
206H-034-00001N	DIN-Jack/BNC-Plug Inline, Nickel	Single	6
251H-034-00001N	DIN-Jack/N-Plug Inline, Nickel	Single	7
2519-034-00001N	DIN-Plug/N-Plug Inline, Nickel	Single	8

