

# UM18-218161101 UM18

**ULTRASONIC SENSORS** 





### Ordering information

Туре	Part no.
UM18-218161101	6048420

Other models and accessories → www.sick.com/UM18



#### Detailed technical data

#### Mechanics/electronics

Supply voltage V <sub>s</sub>	DC 10 V 30 V <sup>1)</sup>
Power consumption	$\leq$ 1.2 W $^{2)}$
Initialization time	< 300 ms
Design	Cylindrical
Housing material	Plastic (PBT, ultrasonic transducer: polyurethane foam, glass epoxy resin)
Thread size	M18 x 1
Connection type	Male connector, M12, 4-pin
Indication	2 x LED
Weight	15 g
Sending axis	Straight
Dimensions (W x H x D)	18 mm x 18 mm x 52.7 mm
Enclosure rating	IP65 / IP67
Protection class	III

 $<sup>^{1)}</sup>$  Limit values, reverse-polarity protected Operation in short-circuit protected network: max. 8 A, class 2.

#### Performance

Operating range, limiting range	120 mm 1,000 mm, 1,300 mm
Target	Natural objects
Resolution	≥ 0.2 mm
Repeatability	± 0.15 % <sup>1)</sup>
Accuracy	± 1 % <sup>2)</sup>
Response time	80 ms
Switching frequency	10 Hz
Output time	20 ms
Ultrasonic frequency (typical)	200 kHz

 $<sup>^{1)}</sup>$  In relation to the current measured value, minimum value  $\geq$  resolution.

<sup>&</sup>lt;sup>2)</sup> Without load.

<sup>&</sup>lt;sup>2)</sup> Referring to current measurement value.

Detection area (typical)	See diagrams	
Additional function	Set switching mode: Distance to object (Dt0) / Window (Wnd) / Object between sensor and background (ObSB), teach-in of digital output, invertible digital output, reset to factory default	

 $<sup>^{1)}</sup>$  In relation to the current measured value, minimum value  $\geq$  resolution.

#### Interfaces

Digital output	
Number	1 <sup>1)</sup>
Туре	PNP
Maximum output current $I_A$	≤ 200 mA
Hysteresis	20 mm

 $<sup>^{1)}</sup>$  PNP: HIGH =  $V_S$  - (< 2 V) / LOW = 0 V.

#### Ambient data

Ambient temperature, operation	-25 °C +70 °C
Ambient temperature, storage	-40 °C +85 °C
Temperature drift	$0.17~\%$ / K $^{1)}$

<sup>1)</sup> Referring to current measurement value.


### Classifications

eCl@ss 5.0	27270804
eCl@ss 5.1.4	27270804
eCl@ss 6.0	27270804
eCl@ss 6.2	27270804
eCl@ss 7.0	27270804
eCl@ss 8.0	27270804
eCl@ss 8.1	27270804
eCl@ss 9.0	27270804
eCl@ss 10.0	27270804
eCl@ss 11.0	27270804
eCl@ss 12.0	27272806
ETIM 5.0	EC001846
ETIM 6.0	EC001846
ETIM 7.0	EC001846
ETIM 8.0	EC001846
UNSPSC 16.0901	41111960

 $<sup>^{2)}</sup>$  Referring to current measurement value.

#### Dimensional drawing (Dimensions in mm (inch))

UM18-2xxxxxx1




- ① Connection
- ② Fixing nuts, width 24 mm
- 3 Status display for supply voltage active (green)
- 4 Status indicator switching/analog output (orange)

#### Connection type




#### Connection diagram



#### **Detection** area

#### UM18-218

#### Detection area in mm (inch)



- Detection area in mm (inch)
- ① Detection range dependent on reflection properties, size, and alignment of the object
- ② Limiting range
- ③ Operating range
- 4 Example object: aligned plate 500 mm x 500 mm
- ⑤ Example object: pipe with 27 mm diameter

#### Recommended accessories

Other models and accessories → www.sick.com/UM18

	Brief description	Туре	Part no.	
Deflector mirro	Deflector mirrors			
600	$90^\circ$ sound deflection plate for UM18-1xxxx and UM18-2xxxx, stainless steel, for straight versions	USP-UM18	5323658	
Mounting brackets and plates				
	Mounting plate for M18 sensors, steel, zinc coated, without mounting hardware	BEF-WG-M18	5321870	
Plug connectors and cables				
	Head A: female connector, M12, 5-pin, straight, A-coded Head B: Flying leads Cable: Sensor/actuator cable, PVC, unshielded, 2 m	YF2A15- 020VB5XLEAX	2096239	

## UM18-218161101 | UM18

**ULTRASONIC SENSORS** 

#### Recommended services

Additional services → www.sick.com/UM18

	Туре	Part no.
Extended warranty		
<ul> <li>Product area: Identification solutions, machine vision, Distance sensors, Detection and ranging solutions</li> <li>Range of services: The services correspond to the scope of the statutory manufacturer warranty (SICK general terms of delivery).</li> <li>Duration: Five-year warranty from delivery date.</li> </ul>	Extended warranty for a total of five years from delivery date	1680671

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

## **WORLDWIDE PRESENCE:**

Contacts and other locations www.sick.com

