

RQRA-1400-1624



ELECTRICAL SPECIFICATIONS


PARAMETER	CONDITION	SYMBOL	VALUE			UNIT
			Min.	Typ.	Max.	
Lower Frequency ^{1,2}	Tuning Voltage:0.3V	fo(Vt)			1400	MHz
Upper Frequency ^{1,2}	Tuning Voltage:5.5V	fo(Vt)	1624			MHz
Tuning Voltage		Vt	0.3		5.5	VDC
Supply Voltage		Vcc	4.75	5.0	5.25	VDC
Supply Current	Vcc=5.0V			25	35	mA
Tuning Sensitivity	Over Tuning Range, 0.3-5.5V	df/dVt		50		MHz/V
Pushing	Over Supply Variation	df/dVcc		0.5	1.0	MHz/V
Pulling ^{1,3}		df/dZI		2.0	4.0	MHz pk-pk
2 nd Harmonic	Vcc=5.0V	a(n*fo)		-15	-10	dBc
Input Capacitance		C _{IN}			120	pF
Operating Temperature Range		Ta	-40		+85	°C
Storage Temperature Range		Tstor	-45		+90	°C
Maximum Voltage	V _{cc(abs)}				6.0	V
Moisture Sensitivity Level	MSL	JEDEC J-STD-2	1			
Termination Finish			Glass-reinforced laminate base and nickel-silver cover			
ESD Sensitivity	HBM	Human body model JESD22-A114		3		kV

OUTPUT CHARACTERISTICS


SINE-WAVE	PARAMETER	SYMBOL	CONDITION	VALUE			UNIT
				Min	Typ.	Max	
	Sine Output Voltage Level	Pw	Output termination 50Ω	-3.0	0	+3.0	dBm
	Supply Current	Is	Vcc, ±5%		25	35	mA
	Output Load	O _{CL}			50		Ω

RQRA-1400-1624

MECHANICAL DIMENSIONS AND PIN FUNCTIONING



■ Marking:



Top View.

RQRA-1400-1624

PHASE NOISE


PARAMETER	SYMBOL	CONDITION	VALUE			UNIT
			Min	Typ	Max	
SSB Phase noise	$\Sigma(\Delta f)$	$\Delta f=10\text{kHz}$		-103	-100	dBc
		$\Delta f=100\text{ kHz}$		-126	-123	

COMMON SPECIFICATIONS

- 1.1 -Load impedance is 50 Ohms.
- 1.2- The frequency range is defined between the (max) lower frequency and (min) upper frequency.
- 1.3 -Pulling is measured with 12dB return loss, all phases.
- 1.4- Package outline tolerances are typ. $\pm 0.30\text{mm}$ / $\pm 0.012\text{inch}$ if not stated differently on the drawing.
- 1.5 -It is recommended to provide two bypass-capacitors (ceramic), from Vcc to Gnd, $1\text{nF} \parallel 100\text{pF}$.
- 1.6- Solder temperature (peak) is 260°C for 10-20s.

RQRA-1400-1624

REFLOW PROFILE



Recommended Solder Reflow Profile			
Temperature Min Preheat	T _{SMIN}		150°C
Temperature Max Preheat	T _{SMAX}		175°C
Time (T _{SMIN} to T _{SMAX})	t _s		60-180 sec.
Temperature	T _L		217°C
Peak Temperature	T _P		260°C
Ramp-up rate	R _{UP}		3°C/sec max.
Ramp-down rate	R _{DOWN}		6°C/sec max.
Time within 5°C of Peak Temperature	t _p		10-20 sec max.
Time t[25°C] to Peak Temperature	t[25°C] to Peak		480 sec.
Time	t _L		60-150 sec.

APPROVALS

Eng. approval, date: CP 07/14/2021

Created by, date: AR 07/14/2021

Revision: A