

Product data sheet

Characteristics

9050JCK58V20

Timing Relay, Type JCK, plug In, repeat cycle, adjustable time, 0.6 to 60 minutes, 10A, 240 VAC, 120 VAC/110 VDC



Main

| | |
|----------------|----------------------|
| Product range | 9050JCK |
| Product type | Timer |
| Timing mode | Repeat cycle |
| Timing range | 0.6...60 min |
| Supply voltage | 120 V AC 110 V DC |

Complementary

| | |
|---------------------------|----------------------|
| Power consumption | 2 VA |
| Current rating | 10 A |
| Switch function | DPDT |
| Contact composition | 2 NO + 2 NC |
| Contact material | Silver nickel |
| Maximum switching voltage | 240 V AC |
| Mounting type | Socket |
| Number of pins | 8 |
| Shape of pins | Tubular |
| For use with | 8501NR51 8501NR52 |

Environment

| | |
|---|----------------------------------|
| Certifications | UL Listed UL Recognized CE |
| Ambient temperature range - operational | -18...150 °F (-28...66 °C) |
| Height | 2.40 in (61 mm) |
| Width | 1.69 in (43 mm) |
| Depth | 4.09 in (104 mm) |

Ordering and shipping details

| | |
|-----------------------|--|
| Category | 21651 - 9050 JCK(NOT JCK60, 70) G P TIMERS |
| Discount Schedule | CP2 |
| GTIN | 785901057970 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 4.32 oz (122.47 g) |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| | |
|------------------------|---------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 2.60 in (6.604 cm) |
| Package 1 width | 4.40 in (11.176 cm) |
| Package 1 Length | 2.00 in (5.08 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|