



- NOTES**
- MATERIAL:**
HSG: NYLON, GLASS-FILLED, UL94V-0 COLOR: BLACK
PIN: 0.50mm SQ, COPPER ALLOY
 - PLATING TYPE:**
 - GOLD FLASH OVER
1.270µm MIN. NICKEL OVERALL.
 - GOLD FLASH ON CONTACT AND
1.905µm MIN. TIN ON SOLDER TAIL OVER
1.270µm MIN. NICKEL OVERALL.
 - 0.254µm MIN. GOLD PLATE ON CONTACT AND
1.905µm MIN. TIN ON SOLDER TAIL OVER
1.270µm MIN. NICKEL OVERALL.
 - 0.381µm MIN. GOLD PLATE ON CONTACT AND
1.905µm MIN. TIN ON SOLDER TAIL OVER
1.270µm MIN. NICKEL OVERALL.
 - 0.762µm MIN. GOLD PLATE ON CONTACT AND
1.905µm MIN. TIN ON SOLDER TAIL OVER
1.270µm MIN. NICKEL OVERALL.
 - 2.540µm MIN. TIN OVERALL
1.270µm MIN. NICKEL OVERALL
 - PRODUCT SPECIFICATION:** PS-87761-100
 - PACKAGING TYPE:** SEE TABLE
 - WAFER TO BE FLAT WITHIN 0.003 mm/mm**
 - COPLANARITY IS TO BE MEASURED BY RESTING THE SOLDER TAIL ON A GAUGE SURFACE**
 - IRREGULAR CIRCUIT CUTOFF WITHIN BREAKAWAY SECTION IS PERMISSIBLE. CUTTING OR CHIPPING OF THE MAIN BODY IS NOT ACCEPTABLE**
 - RECOMMENDED PCB THICKNESS IS 1.60mm±0.10**
 - THE ABOVE CKT 10 IS FOR ILLUSTRATION PURPOSE ONLY**
 - PACKAGING SPECIFICATION:**
TRAY: PK-89990-487
T&R : PK-89990-484 / PK-87858-300
TUBE: RPK-87979-1007 FOR ASSEMBLY 87979-1007.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											
DIMENSION UNITS		SCALE		CURRENT REV DESC: BRIGHT TIN PHASE OUT						molex	
MM		NTS									
GENERAL TOLERANCES (UNLESS SPECIFIED)										CUSTOM HEADER	
										MGRID DUAL ROW HEADER S/WFR, HORIZONTAL SMT	
										PRODUCT CUSTOMER DRAWING	
4 PLACES ±										DOCUMENT NUMBER	
3 PLACES ±										DOC TYPE	
2 PLACES ± 0.2										DOC PART	
1 PLACE ±										REVISION	
0 PLACES ±										SD-87979-002	
ANGULAR TOL ± 3.0°										PSD 001 B1	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER	
				A3-SIZE		87979		SEE TABLE		CUSTOMER	
								GENERAL MARKET		SHEET NUMBER	
										1 OF 2	

F	PART NO.	CKT SIZE	PEG	PLATE OPT.	VOID POSITION	DIMENSION			WITH KAPTON TAPE	PACKAGING OPTION
								MATING END		
						A	B	M		
	87979-0406	4	N	6	----	4.00	2.00	4.00	NO	TRAY
	87979-0407	4	N	6	----	4.00	2.00	4.00	NO	TRAY (B1)
	87979-0806	8	N	6	----	8.00	6.00	4.00	YES	T&R
E	87979-0807	8	N	6	----	8.00	6.00	4.00	YES	T&R (B1)
	87979-1006	10	N	6	----	10.00	8.00	4.00	NO	TRAY
	87979-1008	10	N	6	----	10.00	8.00	4.00	NO	TRAY (B1)
	87979-1007	10	N	6	----	10.00	8.00	4.00	NO	TUBE
	87979-1009	10	N	6	----	10.00	8.00	4.00	NO	TUBE (B1)
D	87979-1206	12	N	2	----	12.00	10.00	4.00	YES	T&R
	87979-1606	16	N	6	----	16.00	14.00	4.00	NO	TRAY
	87979-1608	16	N	6	----	16.00	14.00	4.00	NO	TRAY (B1)
	87979-1607	16	N	6	----	16.00	14.00	4.00	YES	T&R
	87979-1609	16	N	6	----	16.00	14.00	4.00	YES	T&R (B1)
C	87979-2000	20	N	6	----	20.00	18.00	4.00	YES	T&R
	87979-2001	20	N	6	----	20.00	18.00	4.00	YES	T&R (B1)
	87979-2406	24	N	2	----	24.00	22.00	4.00	YES	T&R
	87979-4206	42	N	6	----	42.00	40.00	4.00	YES	T&R
	87979-4207	42	N	6	----	42.00	40.00	4.00	YES	T&R (B1)
B	87979-5006	50	N	6	----	50.00	48.00	4.00	NO	TRAY
	87979-5007	50	N	6	----	50.00	48.00	4.00	NO	TRAY (B1)

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																	
DIMENSION UNITS		SCALE		CURRENT REV DESC: BRIGHT TIN PHASE OUT													
MM		NTS															
GENERAL TOLERANCES (UNLESS SPECIFIED)				EC NO: 679909 DRWN: AKUMAR19 2021/07/28 CHK'D: MRAMAKRISHNA 2021/10/11 APPR: MRAMAKRISHNA 2021/10/11 INITIAL REVISION: DRWN: KCHO 2005/01/31 APPR: SLOW 2005/02/17						CUSTOM HEADER MGRID DUAL ROW HEADER S/WFR, HORIZONTAL SMT							
												PRODUCT CUSTOMER DRAWING					
4 PLACES ±		±								DOCUMENT NUMBER SD-87979-002				DOC TYPE PSD		DOC PART 001	
3 PLACES ±		±															
2 PLACES ±		0.2 ±								MATERIAL NUMBER SEE TABLE		CUSTOMER GENERAL MARKET		SHEET NUMBER 2 OF 2			
1 PLACE ±		±															
0 PLACES ±		±															
ANGULAR TOL ± 3.0°				THIRD ANGLE PROJECTION		DRAWING		SERIES									
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS						A3-SIZE		87979									