



Operating Temp.: -30°C up to +85°C
 Flammability according to: UL94-V2
 Drilling in Panel: 4.0mm
 Panel Thickness: 1.2-1.7mm

Scale - 3:1

Order Code	L (mm)
701 520 500	3.2 ±0.2
701 521 000	4.0±0.2
701 521 500	5.0±0.3
701 522 000	6.3±0.3
701 522 500	7.0±0.3
701 523 000	8.0±0.3
701 523 500	9.5±0.3
701 524 000	10.5±0.3
701 524 500	12.7±0.3
701 525 000	14.0±0.3
701 525 500	15.9±0.3
701 526 000	19.0±0.3
701 526 500	22.0±0.4

				Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions	CREATED DaF	CHECKED SKI	GENERAL TOLERANCE DIN ISO 2768-1m	PROJECTION METHOD		SIZE A4
				Max-Eyth-Str. 1 74638 Waldenburg Germany com. +49 79 42 945 - 0	DESCRIPTION AsSNSN Snap-on keyslot spacer arresting on both sides			TECHNICAL REFERENCE	MATERIAL Nylon 66, natur	
				www.we-online.de eiSos@we-online.de	SIZE xxx xxx xxx			ORDER CODE 70152xx00	DATE 2016-11-10	BUSINESS UNIT eiCan
REV.	FILE	DATE	BY		WEIGHT			STATUS Released	PAGE 1 / 1	

