
TO SNAP LOCK IN A 3 (.118) Ø HOLE, IN A 1.2 - 1.7 (.047 - .067) PANEL THICKNESS



TO SNAP LOCK IN A 4.8 (.187) Ø HOLE, IN A 0.8 - 2.2 (.031 - .086) PANEL THICKNESS

Material: UL94 V-2 Nylon 6/6		
Color: Natural		
	A	
Part No.	mm	in
CBLS205A	3.2	.126
CBLS210A	4.8	0.187
CBLS215A	6.3	.248
CBLS220A	8	.315
CBLS225A	10	.394
CBLS230A	12	.472
CBLS235A	14	.551
CBLS240A	16	.630
CBLS245A	18	.709
CBLS250A	25	.984

TOLERANCES UNLESS NOTED

 $\leq 5 \text{ mm}$ ± 0.2 5 - 20 mm ± 0.3 20 - 40 mm ± 0.4 40 - 60 mm ± 0.5 60 - 100 mm ± 0.8 $\geq 100 \text{ mm}$ ± 1.0 TITLE: DUAL LOCKING CIRCUIT BOARD SUPPORT

FILE: CBLS2XX

SHEET: 1 OF 1 | SHEET SIZE: A | DT: 01/08/15 | DART # | SEE TABLE CA