



**NOTES**

1. MATES WITH 12BW07, 12BW11 JACKS.  
IP66 RATED WHEN MATED WITH JACK.
2. RECOMMENDED WORKING TEMPERATURE: -20° TO +50° C.
3. THE PLUG MUST BE TIGHTENED ALL THE WAY INTO THE HANDLE.
4. MATERIALS:  
PLUG - COPPER ALLOY, NICKEL PLATED  
HANDLE - THERMOPLASTIC RUBBER OVER THERMOPLASTIC, BLACK
5. RoHS COMPLIANT.

PART NUMBER	CABLE RANGE	HOLE DIAMETER (REF)
267S15	Ø 0.140 - Ø 0.170 [3.6 - 4.3]	Ø 0.190 [4.8]
267S18	Ø 0.170 - Ø 0.200 [4.3 - 5.1]	Ø 0.220 [5.6]
267S22	Ø 0.200 - Ø 0.230 [5.1 - 5.8]	Ø 0.250 [6.4]
267S25	Ø 0.230 - Ø 0.260 [5.8 - 6.6]	Ø 0.280 [7.1]
267S28	Ø 0.260 - Ø 0.290 [6.6 - 7.4]	Ø 0.310 [7.9]

**CUSTOMER DRAWING**

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.						
					SIZE	WIDTH	MULT	LBS/M	TEMPER		
					UNLESS OTHERWISE SPECIFIED			FINISH			
					1. ALL DIMENSIONS IN INCHES [mm]			MATERIAL			
					- TWO PLACE DECIMALS ±0.02 [0.5]			SPEC No.			
					- THREE PLACE DECIMALS ±0.005 [0.13]			SCALE			
					FIRST USED ON			1:1			
A	28492	5/18/22	TJK	TJK	DATE DRAWN	BY	CHKD	APVD	<b>Switchcraft®</b>		
REV	ECO NUMBER	DATE	BY	APVD	2/17/20	NS	NS 2/17/20	SRC 2/17/20			
REVISIONS					DO NOT SCALE DRAWING					SHEET 1 OF 1	
					NAME <b>3 CONDUCTOR 1/4" SEALED PLUG, RoHS</b>					PART No. <b>267S15-S28</b>	REV <b>A</b>