

COPALUM TERMINALS AND SPLICES	WIRE SIZE (AWG Unless Indicated Otherwise)			HYDRAULIC TOOLING For Power Units 69120, 314979-1, or 122271-1				PNEUMATIC TOOLING			HEAVY HEAD HAND TOOL	TOOLING AND ACCESSORIES									
	TERMINAL OR PARALLEL SPLICE	BUTT SPLICE		DIES for Head				DIES for Head		JAWS For Head 68068		Hydraulic									
		Aluminum (AL)	Copper (CU)	69066	69082	69099	58422-1	626	69015			DYNA-CRIMP* Hydraulic Power Units 69120-1 (115 VAC, 60 Hz) 69120-2 (230 VAC, 60 Hz)	Hand-Operated Hydraulic Pump 314979-1	Battery-Operated Hydraulic Unit 122271-1	Handle Control with Hose and Cord 59907-[ ]	Hose Assembly with Crimping Head Coupling 59909-[ ]	Foot Control 68284-1				
<b>Bar Crimp</b> For Solid or Stranded Aluminum or Copper Wire  	20-18	20-18	22-20																		
	16-14	16-14	20-18																		
	12-10	12-10	16-14																		
	8	8	12-10																		
	6	6	8																		
	4	4	6																		
	2	2	4																		
	1/0	1/0	2																		
	2/0	2/0	1/0																		
	3/0	3/0	2/0																		
	4/0	4/0	3/0																		
	250 MCM	250 MCM	4/0																		
300 MCM	300 MCM	250 MCM																			
400 MCM	400 MCM	300 MCM																			
500 MCM	500 MCM	400 MCM																			
<b>Insulation Piercing Crimp</b> For Film-Insulated Solid Aluminum and Copper Wire or Stranded Copper Wire  	16-14	16-14	18-16																		
	12-10	12-10	14-12																		
	8	8	12-10																		
	6	6	8																		
	4	4	6																		
	2	2	4																		
	1/0	1/0	2																		
	2/0	2/0	1/0																		
	3/0	3/0	2/0																		
	4/0	4/0	3/0																		
	<b>Sealed Crimp</b> For Stranded Aluminum or Copper Wire  	8	8	10	68006																
6		6	8-6	68007																	
4		4	8-6	68008																	
			4																		
2		2	4	68009																	
1/0		1/0	2	68010																	
			4																		
2/0		2/0	1/0	314964-1																	
3/0		3/0	2/0																		
4/0			1/0																		