



**Mechanical characteristics**

interface dimensions acc. to panel piercing  
isolated installation  
mating life

**Components**

center contact  
outer contact  
other metal parts  
insulator

**Electrical characteristics**

impedance  
frequency  
return loss  
working voltage  
voltage proof  
insulation resistance  
contact resistance  
center contact  
outer contact

**Environmental**  
operating temp.  
RoHS compliant

**Mechanische Eigenschaften**

Steckgesicht nach Montagebohrung  
isolierter Einbau  
Steckzyklen

**Bauteile**

Innenkontakt  
Außenkontakt  
sonstige Metallteile  
Isolierung

**Elektrische Eigenschaften**

Wellenwiderstand  
Frequenz  
Rückflussdämpfung  
Betriebsspannung  
Prüfspannung  
Isolationswiderstand  
Durchgangswiderstand  
Innenkontakt  
Außenkontakt

**Umgebung**

Betriebstemperatur  
RoHS konform

without standard / ohne Norm  
Z155

≥ 500

**Materials / Material**

CuBe2  
brass / Messing  
brass / Messing  
PTFE

**Finish / Oberfläche**

Cu1Ni2Au0,1  
Cu2Ni5  
Cu2Ni5

75 Ω  
0-4,5 GHz  
28 dB Min.  
≤ 170 V<sub>eff</sub> / 50 Hz  
500 V<sub>eff</sub> / 50 Hz  
≥ 10 GΩ

≤ 5.0 mΩ  
≤ 2.5 mΩ

-55°C / +155°C  
2011/65/EU

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]	
			gez./ drawn	07.08.2014	KL		
			gepr./ appr	25.08.2014	VM	co./approx.	
Maßstab/ scale		Benennung/ title					
5:1 (1:1)		Ultra Tiny Bulkhead Jack to Jack HD-BNC -Einbaukupplung (f-f)					
untol. Maße/ dim. without tolerances according to		Untert./ doc. type	Zeichnungsnr./ drawing no.				
		K	J01293A0001				
Ersatz für/ replaces							
				Maße/ dimensions mm			
				Original : DIN A4			
				Blatt/ sheet 1 von/ of 1			