

# Voltage tester - PROFIPOL - 1209101

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Voltage tester, for DC and AC voltages of 6 V to 400 V, IP65

## Why buy this product

- Shock-proof, dust-proof, and splash-proof housing, IP65
- DC and AC voltage tests in the range from 6 V to 400 V
- Polarity test (+/-) for DC voltage
- LED indicator

## Key commercial data

Packing unit	0
Minimum order quantity	1
Catalog page	Page 294 (CL2-2011)
GTIN	 4 046356 309899
Custom tariff number	90303310
Country of origin	IRELAND

## Technical data

### General

Color	black
Ambient temperature (operation)	-10 °C ... 55 °C
Degree of protection	IP65
Voltage supply	2 x micro battery 1.5 V, LR03, AAA
Test certificate	EN/IEC 61243-3 (VDE 0682 Part 401)
Display scope	12 V, 24 V, 50 V, 120 V, 230 V, 400 V AC/DC diode display LED
Phase display	LED
Polarity display	LED (symbol "+/-")
Innenwiderstand_Messkreis	130.00 kΩ
Minimum voltage	6 V DC
Max. voltage	400 V DC
Minimum voltage	6 V AC
Max. voltage	400 V AC

# Voltage tester - PROFIPOL - 1209101

## Classifications

### eclass

eCl@ss 4.0	27200312
eCl@ss 4.1	27200301
eCl@ss 5.0	27200301
eCl@ss 5.1	27200301
eCl@ss 6.0	27200301
eCl@ss 7.0	27200301

### etim

ETIM 2.0	EC000149
ETIM 3.0	EC000149
ETIM 4.0	EC000494

### unspsc

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

## Approvals

### Approvals

---

Approvals

VDE approval of drawings

---

Ex Approvals

---

Approvals submitted

---

### Approval details

VDE approval of drawings 
--

---