Snap-in frame; 4-pole; 1.0 ... 3.0 mm; white

www.wago.com/770-339



Picture differs from the item.		
	Color:	
	Color:	

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/770-339



Plate thickness: 1 3 mm
Cutout tolerance: + 0.1 mm
Please see note below!

Item description

Mounting accessories WINSTA® MIDI 4-pole

Put your trust in tried-and-tested accuracy for the installation in your project: The mounting accessories from the WINSTA® MIDI product line. With WAGO, you can enjoy the advantages of a large selection of expansions for the WINSTA® product line. WINSTA® MIDI with Push-in CAGE CLAMP® spring pressure connection technology is found in a broad range of individual products you can use for quick, easy, flexible, and secure electrical

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/770-339

W/4GO

installation.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

WINSTA® is the pluggable connection system that is optimally tailored to the strict requirements of electrical installation. It allows fast, secure and, above all, error-free installation of components and cables. Choose quality and durability – the WINSTA® MIDI accessory with protection against mismating from WAGO makes the installation of electrical components substantially easier.

- pre-assembled versions
- quick replacement of defective units during ongoing operation

Data Notes

Note	The snap-in connectors must be relieved of tensile and transverse forces. A surface finish can influence the edge radius of the cutouts. This may affect the snap-in socket fit, so ensure an adequate fit before use. In addition, the punched edge should be on the inside for punched
	cutouts. The wings of the snap-in connectors must not be mechanically
	stressed for a long period before use (e.g., due to a pre-locking position).

Connection data

Connection 1

Pole number

Physical data

Width	45.5 mm / 1.791 inches
Height	18.5 mm / 0.728 inches
Depth	37.2 mm / 1.465 inches

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

31.08.2023 Page 3/6

www.wago.com/770-339



Mechanical Data

Housing sheet thickness	1 3 mm / 0.039 0.118 inches
Mounting type	Snap-in flange
Suitable	for socket and plug

Material Data

Note (material data)

Information on material specifications can be found here

Color	white
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.128 MJ
Weight	4.3 g

Environmental requirements

Processing temperature	-5 +40 ℃
Continuous operating temperature	-35 +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

27-44-06-92
EC002863
EC002863
100 pcs
Foil
DE
4055143404952
85366990990

Environmental Product Compliance

RoHS Compliance Status Compliant, No Exemption

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/770-339



Optional accessories

Locking	levers
---------	--------

Locking system

Item no.: 770-140

Locking lever; for sockets and plugs; for tool operation; gray

www.wago.com/770-140

Downloads

Documentation

Bid Text

770-339 X81 - Datei	2019 年2月19日	xml 2.6 kB	Download
770-339 doc - Datei	2017 年4月13日	doc 24.1 kB	Download

CAD/CAE-Data

CAE data

ZUKEN Portal 770-339	URL	Download
CAD data		
2D/3D Models 770-339	URL	Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 770-339 URL Download Snap-in frame; 4-pole; 1.0 ... 3.0 mm; white

Installation Notes

Installation

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/770-339



Insert the socket or plug into the frame (observe the "TOP" marking on the frame!), then snap the assembled unit into the cutout.

Snap the assembled unit into the cutout.

Product family

WINSTA® MIDI

Show all products from the family

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.