

WB SI SL 0.5X3.0**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Similar to illustration

If you demand effective and exact work, it is essential to use the precise torque. This also guarantees high repetition accuracy.

This is the perfect job for the new Weidmüller torque screwdriver with the ergonomic grip and the unique interchangeable bit system.

- Compact and especially light design
- Torque set with special tool (supplied); an unintended, incorrect setting is ruled out.
- Ergonomic handle sizes matched to the torque range.
- Tools subjected to routine testing and provided with an ID number; 100% quality control with verification and product reference.
- Clicking sound upon reaching the set torque, clearly audible and noticeable, no unnecessary tightening.
- Interchangeable blades made from high-quality wear-resistant tool steel.
- All tools fulfil the accuracy requirements of: EN ISO 6798, BS EN 26789, ASME B107.14M
- Trigger accuracy +/- 6% of the set scale value.

General ordering data

| | |
|------------|----------------------------|
| Version | Screwdriver insert |
| Order No. | 2433170000 |
| Type | WB SI SL 0.5X3.0 |
| GTIN (EAN) | 4050118443622 |
| Qty. | 1 pc(s). |

WB SI SL 0.5X3.0**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.comwww.weidmueller.com**Technical data****Dimensions and weights**

| | | | |
|------------|-------|-----------------|------------|
| Depth | 7 mm | Depth (inches) | 0.276 inch |
| Height | 75 mm | Height (inches) | 2.953 inch |
| Width | 7 mm | Width (inches) | 0.276 inch |
| Net weight | 8 g | | |

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Technical data

Description of article VDE-insulated interchangeable bit for slotted screws, size 0.5 x 3

Screwing tools

| | | | |
|---------------------|---------|----------------------|--------|
| Blade thickness (A) | 0.5 mm | Blade width (B) | 3 mm |
| Form | Slotted | Torque setting, max. | 0.6 Nm |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC002116 | ETIM 7.0 | EC002116 |
| ETIM 8.0 | EC003864 | ECLASS 9.1 | 21-04-04-90 |
| ECLASS 10.0 | 21-04-04-90 | ECLASS 11.0 | 21-04-42-04 |
| ECLASS 12.0 | 21-04-42-04 | | |

Downloads

Approval/Certificate/Document of Conformity [Manufacturer's Declaration - Slim Bits](#)

Catalogues [Catalogues in PDF-format](#)