Ratings
Voltage: 300 V
Temperature: -25 ~ 80 °C
Flammability: VW-1

Conductor
Conductor count: 2
Gauge: 20 AWG 0.52 mm²
Material: tinned copper strands
Strand size: ∅0.16 x 26
Resistance at 20 °C: 36.7 Ω /km max

Outer jacket
Material: PVC
Color: white
Diameter: 4 ±0.20 mm
Nominal thickness: 0.50 mm
Resistance at 20 °C: 10 MΩ /km min

Wire marking: E339579 UL AWM STYLE 2468 20 AWG 80°C 300V VW-1 - - - cUL AWM I A 80°C 300V FT1 TENSILITY

Tests
Insulation tensile strength: 2.11 kgf/mm²
Jacket tensile strength: 1.05 kgf/mm²
After aging at 113 ±2 °C for 7 days:
Minimum tensile strength 70 % original
Minimum elongation 65 % original
Heat shock: 121 ±1 °C /1 hour, no observed degradation
Deformation: 121 ±1 °C /1 hour, ≤ 50 %
Cold bend: -10 ±2 °C /1 hour, no observed cracking





Revision:	Date:	Description:
A	07/09/2014	Initial release
A1	01/08//2016	Corrected tolerances
A2	09/06/2018	Increased operating temperature range

Prepared:
AW
Digitally signed by AW
Date: 2018.09.06 11:25:20 -07'00'

Verified:
PS
Digitally signed by PS
Date: 2018.09.06 12:07:59 -07'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:
RoHS and REACH compliant

Function test: no open, no short circuit, no intermittent

Description:
Wire, 2C TS, 20 AWG, UL2468, 300V, 80C, 4.0 mm, VW-1, PVC, white

TENSILITY
tel 1.541.323.3228 *800* 877.670.7118
fax 1.541.323.4202 *web* tensility.com

Size: A
Part number: 30-00399
Scale: 12:1
Sheet 1 of 1

To see a custom version of this cable assembly, call Tensility at 541-323-3228 or email engineering@tensility.com