



1. THE CONTACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT.
2. MATERIAL: HOUSING & COVER - THERMOPLASTIC, BLACK. TERMINALS - PHOS BRONZE PLATED WITH EITHER .000050 MINIMUM GOLD PLATE OR GOLD FLASH OVER PALLADIUM NICKEL PLATE, .000050 MIN TOTAL ON MATING SURFACE. GOLD FLASH PLATED ON TERMINATING SIDE. .000050 MINIMUM NICKEL UNDERPLATE OVER ENTIRE TERMINAL.
3. COVER SHOWN LOOSE BUT SHIPPED ASSEMBLED.
4. WIRE RANGE: 26 AWG SOLID THRU 30 AWG SOLID AND 2B AWG STRANDED RIBBON CABLE.
5. ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY UNLESS OTHERWISE SPECIFIED.
6. FLAT CABLE SHALL BE FURNISHED BY CUSTOMER.
7. MATING FACE CONSISTS OF TWO ROWS OF TERMINALS ON .085 CENTERS, TERMINATING SIDE CONSISTS OF TERMINALS ON .100 CENTERS FOR AN EFFECTIVE .050 TERMINATION.
8. FOR MORE INFORMATION REFER TO AMP PRODUCT SPECIFICATION 108-8076 & APPLICATION SPEC 114-6030.

REVISED		REVISIONS		DATE	BY	CHKD
GP	00	1	DESCRIPTION	1/24/83	BM	WM
H		2	REVISED PER ECU-88-00127			

THIS DRAWING IS A CONTROLLED DOCUMENT		DATE		SCALE	
DIMENSIONS IN INCHES		REV	15/04/87	SCALE	2:1
ORANGE STRIPES		BY	W. MILLIEMES	DATE	15/04/87
RED STRIPES		BY	W. MILLIEMES	DATE	15/04/87
GREEN STRIPES		BY	W. MILLIEMES	DATE	15/04/87
BLACK STRIPES		BY	W. MILLIEMES	DATE	15/04/87
APPLICATION SPEC		BY	W. MILLIEMES	DATE	15/04/87
CUSTOMER DRAWING		BY	W. MILLIEMES	DATE	15/04/87

AS SHOWN 553800-1
 DESCRIPTION PART NUMBER

Yeo Electronics
 7500 Denison Corporate
 Hwy. 170B-4988
 Scarborough, ON M1V 4S9

PLUG ASSEMBLY, 36 POSITION
 SCREEN CLAMP LATCH