

Data sheet

15683.2 USR 2



Undervoltage monitoring relay module with adjustable switching threshold (160 - 240 V), Screw connection, Mounting type: Mounting rail TS 35, 1 CO contact

Business data

Article number	<u>15683.2</u>
Article name	USR 2
GTIN (EAN)	4044211124410
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	60.2 g
Weight per piece (including packaging)	67.7 g
Unit of weight	G
Customs number	85364900
Country of origin	AT
Product description	Undervoltage monitoring relays

Technical data

Dimensions

Length	87 mm
Width	17.5 mm
Height TS 35 / 7.5 with BA	67.5 mm
Installation dimensions acc. to DIN 43880	1 Te

Ratings

Rated voltage	250 V
Nominal input voltage	3(N) - 400/230 V
Rated frequency min.	48 Hz
Rated frequency max.	63 Hz
Rated impulse voltage	4 kV
Overvoltage category	III
Contamination degree	3

Connection data

Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.2 mm ²
Wire cross-section single-core (rigid), max.	4 mm ²
Wire cross-section stranded, min.	0.5 mm ²
Wire cross-section stranded, max.	4 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.5 mm ²
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm ²
Stripping length	8 mm
Torque	1 Nm

Input data

Drop-out voltage	Defined by measuring function
Power supply AC/DC	= measuring voltage V
Power consumption	0,8 W
Tolerance	(0,7 - 1,1) Un
Power-on duration	100%
Recovery time	500 ms

Technical data

Output data

Electrical lifespan (AC1)	2x10 ⁷ at 1000 VA resistive load
Mechanical lifespan	20x10 ⁷
Relay contact	1 CO contact
Switching capacity of aligned device (gap < 5 mm)	1250 VA (5 A / 250 V AC)
Switching capacity of non-aligned device (gap < 5 mm)	1250 VA (5 A / 250 V AC)

Time functions

Time range	Fast, approx. 200 ms (tripping delay)
------------	---------------------------------------

Accuracy

Basic accuracy	± 5% (of rated voltage)
Repeat accuracy	± 2%
Temperature influence	± 1% °C

Measuring circuit

Measured value	AC Sinus, 48 - 68 Hz
Measurement input	= supply voltage
Overload capability	Defined by tolerance of the supply voltage
Switching threshold U_s	160 - 240 V (L-N)
Hysteresis	ca. 5%

Materials

Working temperature, min.	-25 °C
Working temperature, max.	55 °C
Relative humidity, min.	15 %
Relative humidity, max.	85 %

Further technical data

Status display	✓
Storage temperature, min.	-25 °C
Storage temperature, max.	70 °C
Shock resistance	15 g 11 ms
Fuse	5 A
Trigger characteristic	Fast-acting (F)
Vibration resistance	10 - 55 Hz 0,35 mm
Remarks	Refer to the package insert for LED functions.

Technical data

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-01-17
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet

15683.2 USR 2



Approvals


Standards and regulations

CE compliant	yes
--------------	-----

Data sheet

15683.2 USR 2

Media



Accessories
