

tightening torque/thread 6.0 Nm/M 6 Inspection Test Pattern Size B 10

Type	Cat.-No.		Qty.p.pck.
SR 50	41120.2	beige	10
SR 50	41120.5	blue	10


Ratings:

	UL	CSA	DIN-VDE	IEC
Rated Voltage	600 V	600 V	1000 V	1000 V
Rated Current	150 A	150 A	168 A	150 A

Max Rated Cross Section

Single Wire (solid)	16-50 mm ²
Stranded Wire (flexible)	25-50 mm ²
Wire Size	AWG 6-1/0

Dimensions	TS 32	TS 35
LxBxH (mm)	79x20x82	79x20x76
Stripped Length	27 mm	



tightening torque/thread 12 Nm/M 8 Inspection Test Pattern Size B 12

Type	Cat.-No.		Qty.p.pck.
SR 95	41122.2	beige	10
SR 95	41122.5	blue	10

Ratings:

	UL	CSA	DIN-VDE	IEC
Rated Voltage	600 V	600 V	1000 V	1000 V
Rated Current	230 A	230 A	250 A	232 A

Max Rated Cross Section

Single Wire (solid)	25-95 mm ²
Stranded Wire (flexible)	35-95 mm ²
Wire Size	AWG 2-4/0

Dimensions	TS 32	TS 35
LxBxH (mm)	84x25x94	84x25x88
Stripped Length	30 mm	

Type:	Cat.-No.	Qty.p.pck.	Terminal accessories	Type:	Cat.-No.	Qty.p.pck.
			End plate			
			Isolation partition			
			Separator			
HES 32 ST	2760.0	50	End bracket	HES 32 ST	2760.0	50
HES 35 ST	2761.0	50	End bracket	HES 35 ST	2761.0	50
			Test socket			
			Test plug			
			Switchable link			
			Connection sleeve			
			Screw			
AD 1/50	2810.0	50	Warning tag	AD 1/95	2804.0	50
for 1 terminal block			Warning tag	for 1 terminal block		
			Plastic screw for warning tag			
AQI 2/50	2763.2* 168A	5	External jumper	AQI 2/95	2765.2* 250A	5
AQI 3/50	2764.2* 168A	5	External jumper	AQI 3/95	2766.2* 250A	5
ISKS 5	2818.0	-	Allen key	ISKS 6	2772.0	-

*When using AQI the rated cross-section is reduced.