

## Oximeter 5 Click



PID: MIKROE-4986

**Oximeter 5 Click** is a compact add-on board suitable for measuring blood oxygen saturation. This board features the MAX30102, integrated pulse oximetry, and heart-rate monitor module from [Analog Devices](#). The MAX30102 includes internal LEDs, photodetectors, optical elements, and low-noise electronics with ambient light rejection. It operates on a single 1.8V power supply acquired from both mikroBUS™ power rails for the internal LEDs, communicating through a standard I2C compatible interface. The MAX30102 can be shut down through software with zero standby current, allowing the power rails to remain powered at all times. This Click board™ makes it an excellent choice for optical pulse oximetry and health monitoring applications.

Oximeter 5 Click is supported by a [mikroSDK](#) compliant library, which includes functions that simplify software development. This [Click board™](#) comes as a fully tested product, ready to be used on a system equipped with the [mikroBUS™](#) socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.  
 ISO 14001: 2015 certification of environmental management system.  
 OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).

## Specifications

|                  |   |
|------------------|---|
| Type             | Biometrics  |
| Applications     | Can be used for optical pulse oximetry and health monitoring applications   |
| On-board modules | MAX30102 - high-sensitivity pulse oximeter and heart-rate sensor from Maxim Integrated, now part of Analog Devices  |
| Key Features     | Integrated optical components, fully integrated ADC, LED drivers, and timing core, low power consumption, fast data output capability, designed for ultralow direct optical reflections, and more |
| Interface        | I2C   |
| ClickID          | No  |
| Compatibility    | mikroBUS  |
| Click board size | M (42.9 x 25.4 mm)  |
| Input Voltage    | 3.3V or 5V  |

## Resources

[mikroBUS™](#)

[mikroSDK](#)

[Click board™ Catalog](#)

[Click Boards™](#)

## Downloads

[MAX30102 datasheet](#)

[SN74LVC1T45 datasheet](#)

[PCA9306 datasheet](#)

[MAX8511 datasheet](#)

[Oximeter 5 click schematic](#)

[Oximeter 5 click 2D and 3D files](#)

[Oximeter 5 click example on Libstock](#)

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.  
 ISO 14001: 2015 certification of environmental management system.  
 OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).