

REV. Status

ADSL Inductor


REVISION -
01/14/02 MP

REVISION A
ADDED
COUNTRY
OF ORIGIN.
03/21/02 MP

REVISION B
CHANGED A.3
05/28/02 MP

A. Electrical Specifications (@ 25°C)



1. Primary Open Circuit Inductance; 5.0mH ±5% @ 10KHz, 0.1Vrms, 100mA DC Measured (1-5) and (6-10)
2. DC Resistance; (1-5)=5.0Ω MAX
(6-10)=5.0Ω MAX
3. Turns Ratio; (1-5):(6-10)=1:1.00±1%
4. Dielectric Strength; 630Vrms 1 second @ Wdg. to Wdg.
5. Operating Temperature Range; -40°C to +85°C




MODEL NUMBER
TTC-4111

B. Marking; TTC-4111, TAMURA, country of origin and date code

C. Schematic and Mounting Footprint;



D. Mechanical Specifications;



PREPARED BY:

D. Rund

ENGINEER:

M. Pitchai

QUALITY CONTROL:

D. Kelley

APPROVED:

J. Coleman

DWG CONTROL NO.
P-A1-12981
ACAD\TTC\A1129811.DWG

REV
B

ADSL
INDUCTOR
TAMURA CORPORATION OF AMERICA
43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624
(909) 699-1270 FAX 9096769482

TTC-4111
MODEL SPECIFICATION
DIM: mm(in) SCL: 3/1 SH: 1 OF 1

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.