

APPLICATOR PARTS LIST

TYPE

SIDEMISE

.156 Dia.
Pin & Soc.

AMP INCORPORATED
HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	
1	WIRE CRIMPER PIN Δ	1	456411-6	42	Shear Plate - Left	1	454206-1	
2	INS. CRIMPER	1	2-473740-1	43	Shear Block - Right	1	386372	
3	ANVIL	1	690386-1	44	Floating Shear	1	465406	
4	ANVIL SPACER	1	811780-1	45	Retaining Plate - Front	1	811714-3	
5	SHEAR BLADE			46	Retaining Plate - Rear	1	810822-1	
6	REAR SHEAR PLATE			47	Spring - Shear Return	1	374322	
7	SHEAR BLADE SPACER			48	Shear - Depressor	1	811946-3	
8	FRONT SHEAR PLATE			49	Key - Shear Retainer	1	386358	
9	REAR ANVIL SPACER PLT.			50	Guard Mount	1	811306-1	
10	FRONT Strip Hold	1	811593-3	51				
11	TOOL SPACER PIN Δ	1	387744	52				
12	CRIMP SPACER	1	370827	53				
13	FRONT STRIP GUIDE	1	810971-6	54	Rear Strip Guide Spacer	1	811527-2	
14	REAR STRIP GUIDE	1	465440-8	55	Hold Down Ass'y.	1	811849-1	
15	RAM 473699	1	473699	56	Holder		811850-1	
16	TOOL HOLDER			57	Cover		811851-1	
17	ADJ. CRIMP MOUNT Ass'y.	1	465392-9	58	Blade REF		811852-1	
18	ADJ. BLOCK			59	Spring	1	6-22279-6	
19	APPLICATOR MOUNT ASSY.			60	Fl. Hd. Soc. Cap. Ser. & lg.	1	1-21003-8	
20	BASE PLATE	1	465100	61				
21	BASE BLOCK	1	465101	62	WIRE CRIMPER Soc. Δ	1	453941-0	
22	STRIP GUIDE PLATE	1	465513-4	63	TOOL SPACER Soc. Δ	1	470493-6	
23	ANVIL HOLDER			64				
24	Wire Stop Guide	1	811787-2	65	Tension Adj. Plate	1	374999	
25	STRIPPER - Wire Stop	1	386361-1		MISCELLANEOUS		453594	
26	STRIPPER MOUNT	1	386362	66	2" Dia. Reel Support Ass'y	1	56500-6	
27	RETAINER PLATE	1	389078	67				
28	STRIPPER MOUNT BRACKET	1	387715-1	68				
29	STRIPPER BUSHING	1	389049-1	69	Paper Separator	1	674927-1	
30	STOCK DRAG	1	386955	70				
31	STOCK DRAG HANDLE			71				
32	STOCK DRAG STUD 374900	1	374900	72				
33	STOCK DRAG SPRING 370572	1	370572		REVISION RECORD	DATE	BY	ECN
34	STOCK DRAG ADJ. SCREW Nut	1	21022-3	A	SUPERSEDES 545793-3	10-16-68	RB	L6253
35	FEED FINGER HOLDER	1	386942	B	32, 33 & FEED	6-3-69	RB RT	L6692
36	FEED FINGER	1	386941	C	ITEM 10 WAS -1 42 WAS RISES	5-20-70	RB IM	L7551
37	FEED FINGER TIP	1	387251	D	PER ECN	9-10-70	RB IM	L7774
38	FEED FINGER SCREW Guide	1	689915-2	E	REV PER SUPP	8-16-71	RB IM	L8332
39	BASE CASTING	1	570238	F	HARDWARE WAS 687509-1	1-3-72	RB IM	L8659
40	GUARD 457665-2	1	811306-1	G	REV. PER ECN	3-20-72	RB IM	L8781
41	Bracket Guard	1	811306-1	H	REV PER ECN	4-2-73	RB IM	L9621
				J	ADD ITEM 62563	8-23-74	RB	R724
				JT	INACTIVE PRO	2-24-77	RB	R195

CRIMPING DATA		TERMINALS
TO APPLY TERMINAL		Socket
WIRE SIZE	CRIMP HEIGHT	Feed
12	.087	.660
		61210
10	.106	
CRIMP	SIZE	TYPE
WIRE	.140	F
INSUL.	.210	F
SLEEVED		.500
INSULATION RANGE	WIRE RANGE	FEED
.185 Max.	12 - 10	.660
		500
EXPLODED VIEW		FEED .500
A-6002-4-6		Pin
REMARKS:		Feed
Δ Mounts on Item 13		61211
Top Tool Mounting Sequence		
From Ram Outward: Item		
55, 11, 12, 17 & 48.		
Δ 61210 USE 62 & 63		
61211 USE 1 & 11		
INACTIVE		
FOR REPLACEMENT ONLY		
DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT		
THIS APPLICATOR IS TO BE USED ON		DIST.
AMP-O-LECTRIC 1-471273-3		4
SERIAL NO.	DATE SHIPPED	DESIGNED
		8/10/68
CUSTOMER NAME AND ADDRESS		CHK'D
		10-21-68
APPLICATOR NUMBER		APP'D
REV. K	565793-4	10/21/68
		1 of 1

K EC A-360692

Use Hardware Sheet #687511-8 OK