

Product data sheet

Specifications



terminal block

AB3RV162U

Complementary

[In] rated current	150 A for 1P busbar
Electrical connection	1 solid upstream 35 mm ² connector 1 flexible upstream 25 mm ² connector 6 solid downstream 0.5...6 mm ² tap-off 6 flexible downstream 0.5...4 mm ² tap-off
Fixing mode	Clip-on
Mounting support	rail
Product compatibility	Universal fixing frames
Product destination	terminal block

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.500 cm
Package 1 Width	12.700 cm
Package 1 Length	15.500 cm
Package 1 Weight	91.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	13.500 cm
Package 2 Width	12.700 cm
Package 2 Length	15.500 cm
Package 2 Weight	917.000 g
Unit Type of Package 3	S02
Number of Units in Package 3	40
Package 3 Height	15 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	3.970 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Recommended replacement(s)