

Magnetic Actuation


41FY1



- Magnet Actuator
- Compatible with 40FY Series



Dimensions



Technical Data

General specifications

Rated operating distance	S_n	6.4 ... 15.2 mm
--------------------------	-------	-----------------

Nominal ratings

Switching state indicator	NO contact
---------------------------	------------

Standard conformity

Standards	EN 60947-5-2
-----------	--------------

Approvals and certificates

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose

Ambient conditions

Ambient temperature	-30 ... 70 °C (-22 ... 158 °F)
---------------------	--------------------------------

Release date: 2022-05-23 Date of issue: 2022-05-23 Filename: 450046_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 PEPPERL+FUCHS

Technical Data**Mechanical specifications**

Housing material	Polycarbonate
Sensing face	Polycarbonate
Degree of protection	IP67

Release date: 2022-05-23 Date of issue: 2022-05-23 Filename: 450046_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.comUSA: +1 330 486 0001
fa-info@us.pepperl-fuchs.comGermany: +49 621 776 1111
fa-info@de.pepperl-fuchs.comSingapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com **PEPPERL+FUCHS**