


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00187	Connector, dc plug, 5.5x2.5xL20.5 mm, molding style, spring contacts	1	
2	30-00395	Wire, 2C TS, 18 AWG, UL2468, 300V, 80C, 4.4 mm, VW-1, PVC, 87A	1	
3	24-00006	Overmold, PVC	1	black



Wiring Diagram	
50-00187	wire color
center	black with stripe
sleeve	black

**Notes:**  
Functionally equivalent components may be substituted

Revision: A	Date: 02/06/2018	Description: Initial release	Prepared: <b>GL</b> <small>Digitally signed by GL Date: 2018.02.06 16:38:27 -08'00'</small>	Notes: RoHS compliant Function test: no open, no short circuit, no intermittent	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
			Verified: <b>JP</b> <small>Digitally signed by JP Date: 2018.02.13 14:59:38 -08'00'</small>	Description: Cable, 1830 mm, 5.5x2.5x12 mm 90° 50-00187 dc plug to 10 mm tinned, 18 AWG, UL2468, 30-00395 wire	
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm		Size: A Part number: 10-02506
					Scale: 1:1