



#### General ordering data

Order No.	1632390000
Part designation	WTA 6/ZA WTR2.5
Version	Modular terminal, accessories, Test adapter
EAN	4008190209674
Qty.	25 pc(s).

#### Product notes

Note, technical data	Rated current 6 A
----------------------	-------------------

#### CSA rating data

Voltage (CSA)	300 V
CSA current	6 A

#### Conductors for clamping (additional connection)

Clamping range, max.	1.5 mm <sup>2</sup>
Rated cross-section	1.5 mm <sup>2</sup>
Clamping screw	M 2.5

#### Conductors for clamping (rated connection)

Type of connection	Screw connection
No. of connections	1
Stripping length	6 mm
Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	1.5 mm <sup>2</sup>
Flexible, min.	1 mm <sup>2</sup>
Flexible, max.	1.5 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	1.5 mm <sup>2</sup>

#### Dimensions

Width	5 mm
Height of lowest version	107.6 mm
Length	66.1 mm

## Dimensions

### Rating data

Rated cross-section	1.5 mm <sup>2</sup>
Rated voltage	250 V
Rated current	6 A

### Stud connection

Tightening torque range	0.4 Nm
-------------------------	--------

### Test adapter

Function	Test adapter
With snap-in pegs	Yes

### Test adapter dimensions

Height with TS 35	107.6 mm
With snap-in pegs	Yes

### Test adapter rated data

Rated voltage	250 V
---------------	-------

### UL rating data

Voltage (UL)	300 V
Current (UL)	6 A

### Approvals

Approvals institutes



### Classifications

ETIM 2.0	NK
ETIM 3.0	EC002255
eClass 4.1	27-14-11-99
eClass 5.0	27-14-11-45
eClass 5.1	27-14-11-45

### Similar products

Order No.	Part designation	Version
1632380000	WTA 6 WTR2.5	Modular terminal, accessories, Test adapter