



# Industrial DIN Rail Mount Ethernet Extender

EIR-EXTEND



## PRODUCT FEATURES

- Redundant power inputs
- Wide operating temperature
- Extend Ethernet up to 6232 ft. (1.9 km) over standard copper wires
- Ethernet port: RJ-45 10/100Mbps
- Full/Half-duplex, Auto-negotiation / Auto-MDI/MDX
- Ethernet extend port: RJ-11 50Mbps full duplex VDSL
- UL/CUL Class 1/Division 2 Groups A, B, C, D
- NEMA TS2

The EIR-EXTEND is a point-to-point Ethernet Extender designed to operate in harsh environments. Functioning at temperatures from -40 to 75° C, it has been tested for functional operation up to 85° C. Using existing copper wire runs, it allows the extension of Ethernet signals. The EIR-EXTEND is the perfect solution for installing Ethernet connectivity on the factory floor. Used in pairs, configuration is easy. Configure one unit as the local device, and the other one as the remote device. External power supplies are required (not included).

## ORDERING INFORMATION

MODEL NUMBER	ETHERNET PORTS
EIR-EXTEND	DIN Rail Mount Ethernet Extender

## ACCESSORIES

- MDR-40-24 - DIN Rail Power supply 24VDC 40 Watt
- PS12VDC3P - Hardened AC Power Supply, 12VDC, 36W, 3A, 90-264VAC input, DC jack
- C5UMB3FBL - 3 ft. (1 M) - Blue - Category 5e UTP Patch Cord



### IN THE FIELD

#### Government Remote Site Metering

Industry: Energy and Natural Resources  
Product: Ethernet Extender



[www.bb-elec.com/  
Metering](http://www.bb-elec.com/Metering)

EIR-EXTEND

Carrier data charges may apply.



### IN THE FIELD

#### Recording Wastewater Chlorine and PH Levels

Industry: Energy and Natural Resources  
Product: Ethernet Extender



[www.bb-elec.com/  
Wastewater](http://www.bb-elec.com/Wastewater)

EIR-EXTEND

Carrier data charges may apply.

# Industrial DIN Rail Mount Ethernet Extender

EIR-EXTEND



## SPECIFICATIONS

TECHNOLOGY	
Standards	802.3 10BaseT 802.3u 100BaseTx 802.3x Ethernet over VDSL
Protocol	Transparent to higher level Protocols
Processing	Half-duplex: backpressure Full-duplex: 802.3x
POWER	
Input Voltage	12 VDC – Power Jack 12 – 30 VDC Terminal Block
Input Connection	350 mA (Power Jack) 175 mA (Terminal Block)
Power Consumption	4.2 W Max
MECHANICAL	
Case	DIN Mount IP30 Aluminum
Dimensions	5.0 x 11.12 x 13.5 cm (1.97 x 4.38 x 5.31 in)
Weight	0.8 kg (1.76 lbs)
ETHERNET INTERFACE	
Port	RJ-45, 10/100BaseTX Full/Half Duplex Auto-Negotiation Auto-MDI/MDX
Speed	10/100 Mbps
Distance	320 ft. (100 m)
Cable	CAT 5

EXTENDER INTERFACE	
Port	RJ-11 or Terminal Block
Speed	Up to 50 Mbps
Distance	Up to 6,232 ft. (1.9 km)
Cable	24 AWG Copper Pair 100 Ohm Impedance
ENVIRONMENT	
Operating Temperature	-40 to 75°C Tested to 85°C
Storage Temperature	-40 to 85°C
Operating Humidity	0 to 95% Non-condensing
REGULATORY APPROVALS	
Emissions	FCC Part 15, Class A, NEMA TS2
CE	EN61000-6-(2,3) EN6100004-(2,3,4,5,6,8,11) UL/CUL Class 1/Division 2 Groups A, B, C, D

TOP LEDS (BNC LINE CONNECTIONS)			
	LED	Speed	Distance
1	Green	1 Mbps	6232 ft. (1.9 km)
	Amber	3 Mbps	5904 ft. (1.8 km)
2	Green	5 Mbps	5249 ft. (1.6 km)
	Amber	10 Mbps	4593 ft. (1.4 km)
3	Green	15 Mbps	3936 ft. (1.2 km)
	Amber	20 Mbps	3280 ft. (1.0 km)
4	Green	25 Mbps	2624 ft. (0.8 km)
	Amber	30 Mbps	2296 ft. (0.7 km)
5	Green	40 Mbps	1968 ft. (0.6 km)
	Amber	50 Mbps	984 ft. (0.3 km)