



#### General ordering data

Order No.	8433290300
Part designation	SIM S7/300 FB40 3.0M
Version	PLC front adapter, 32 / 1x4 byte, 60 V AC/ 75 V DC , 1 A
EAN	4008190113001
Qty.	1 pc(s).

#### Connection data

Connection on control side	Plug-in connector, acc. to IEC 603-1/ DIN 41651
Connection on process side	SIEMENS front-connector housing
Design	1x40-pole pre-assembled cable with female multipoint connector
Implementation of connection level / plug connector	Signal byte 0 .0 - .7 IEC603/1 => 40- 33 Signal byte 1 .0 - .7 IEC603/1 => 30- 23Signal byte 2 .0 - .7 IEC603/1 => 20- 13Signal byte 3 .0 - .7 IEC603/1 => 10- 3IEC603/1 32, 22, 12, 2 + supply par. PCB terminalIEC603/1 31, 21, 11, 1 - supply par. PCB terminal
Type	40-pole pre-terminated cable; supply voltage via PCB terminal

#### Front adapter for PLC I/O module

Digital input	S7/300 6ES7 321-1BL00-0AA0, 32DI
Digital input/output	S7/300 6ES7 323-1BL00 0AA0, 16DI/16DO
Digital output	S7/300 6ES7 322-BL00 0AA0, 32DO

#### Ordering data

Front adapter with pre-assembled control wire, length 3m	SIM S7/300 FB40 KONV 3.0 8433290300
--	-------------------------------------

#### Dimensions

Length	115 mm
Height	32 mm
Width	22 mm

### Dimensions

### Approvals

Approvals institutes **n.a.**

### Classifications

ETIM 2.0	EC001423
ETIM 3.0	EC000237
eClass 4.1	27-24-04-09
eClass 5.0	27-24-22-08
eClass 5.1	27-24-22-14

### Similar products

Order No.	Part designation	Version
8433290200	SIM S7/300 FB40 2.0M	PLC front adapter, 32 / 1x4 byte, 60 V AC/ 75 V DC , 1 A
8433290250	SIM S7/300 FB40 2.5M	PLC front adapter, 32 / 1x4 byte, 60 V AC/ 75 V DC , 1 A
8433290500	SIM S7/300 FB40 5.0M	PLC front adapter, 32 / 1x4 byte, 60 V AC/ 75 V DC , 1 A