# DT04-12PB-BL11 ACTIVE

TE Internal #: DT04-12PB-BL11

Housing for Male Terminals, Wire-to-Wire, 12 Position, .359 in [9.12 mm] Centerline, Sealable, Black, Wire & Cable, Power & Signal,

Panel Mount

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH DT Receptacle Connectors











Connector & Housing Type: Housing for Male Terminals

Mating Pin Diameter: 1.59 mm [ .063 in ]

Connector System: Wire-to-Wire

Number of Positions: 12

Centerline (Pitch): 9.12 mm [ .359 in ]

All DEUTSCH DT Receptacle Connectors (241)

# Features

# **Product Type Features**

| Connector Shape                   | Rectangular                |
|-----------------------------------|----------------------------|
| Connector & Housing Type          | Housing for Male Terminals |
| Connector System                  | Wire-to-Wire               |
| Sealable                          | Yes                        |
| Hybrid Connector                  | No                         |
| Primary Locking Feature           | Integrated in Housing      |
| Connector & Contact Terminates To | Wire & Cable               |

### **Configuration Features**

| Blank Cavity Position  | 0                      |
|------------------------|------------------------|
| Connector Modification | Sealed Flange, End Cap |
| Connector Seal Code    | E Seal                 |
| Number of Positions    | 12                     |
| Number of Rows         | 2                      |



#### **Electrical Characteristics**

| Operating Voltage            | 250 VAC          |
|------------------------------|------------------|
| Nominal Voltage Architecture | 12 V, 24 V, 48 V |

## **Body Features**

| Cable Exit Angle        | 180°  |
|-------------------------|-------|
| Primary Product Color   | Black |
| Connector & Keying Code | В     |

### **Contact Features**

| Contact Size                 | Size 16          |
|------------------------------|------------------|
| Contact Type                 | Pin              |
| Mating Pin Diameter          | 1.59 mm[.063 in] |
| Contact Current Rating (Max) | 13 A             |

#### Mechanical Attachment

| Terminal Position Assurance | Yes              |
|-----------------------------|------------------|
| Strain Relief               | Add By Accessory |
| Mating Alignment Type       | Keyed            |
| Mating Alignment            | With             |
| Connector Mounting Type     | Panel Mount      |

## **Housing Features**

| Housing Material   | PA GF            |
|--------------------|------------------|
| Centerline (Pitch) | 9.12 mm[.359 in] |

## Dimensions

| Connector Height                     | 44.07 mm[1.735 in]            |
|--------------------------------------|-------------------------------|
| Product Width                        | 88.34 mm[3.478 in]            |
| Product Length                       | 52.37 mm[2.062 in]            |
| Row-to-Row Spacing                   | 4.45 mm[.175 in]              |
| Compatible Insulation Diameter Range | 1.35 – 3.05 mm[.053 – .12 in] |

# **Usage Conditions**

| Operating Temperature (Max) | 125 °C[257 °F]             |
|-----------------------------|----------------------------|
| Operating Temperature Range | -55 – 125 °C[-67 – 257 °F] |

# Operation/Application

|  | Circuit Application | Power & Signal |
|--|---------------------|----------------|
|--|---------------------|----------------|



#### **Industry Standards**

| Degree of Protection                 | IP68, IP6K9K                       |
|--------------------------------------|------------------------------------|
| Agency/Standard                      | SAE J2030                          |
| UL Flammability Rating               | 12mm Flame Test per Standard UL-94 |
| Packaging Features                   |                                    |
| Packaging Quantity                   | 100                                |
| Packaging Method                     | Box                                |
| Other                                |                                    |
| Serviceable                          | Yes                                |
| Connector Position Assurance Capable | No                                 |

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant  |
|---|--|
| EU ELV Directive 2000/53/EC                   | Compliant  |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold  |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.   |
| Solder Process Capability                     | Not reviewed for solder process capability   |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





TE Part # CAT-D487-P729

Dust Caps — DEUTSCH DT



TE Part # CAT-D48-SP729
DEUTSCH Sealing Plugs



TE Part # CAT-D48-ST273
DEUTSCH Solid Contacts



TE Part # CAT-J41-DDPC
DEUTSCH DT Plug Connectors



TE Part # W12P WEDGE LOCK, 12P, REC, GRN, DT



TE Part # 776364-1 SEALING PLUG, SZ 20 CAVITY



TE Part # CAT-J67-DSCC16
DEUTSCH Size 16 Crimp Contacts



TE Part # DT-RT1
EXT TOOL, FRONT RELEASE




TE Part # 2300908-1 0460-003-16329, PIN, SOLID, 20-24AWG, AU

TE Part # DT06-12SB-CE18
PLG,12P, BLK, E, SEAL RET,ENH KEY,
RCAP,B

TE Part # CAT-D48-SFT273

DEUTSCH Stamped and Formed
Contacts


# Customers Also Bought



TE Part #927854-2
PL 250 REC TERMINAL 17-13 AWG



TE Part #DT04-4P-RT03
REC, 4P, GRY, 600V, 1.28V, 4A DIODE



TE Part #281937-1 MIC MARKII TAB CONTACT



TE Part #7-2151731-7
OCEAN\_2.0\_SPARE\_PART\_KIT100F130O





TE Part #1-2176421-8 TLRP 2512 2.0W R020 1% 25PPM 4K RL



TE Part #1-2176421-9
TLRP 2512 2.0W R022 1% 25PPM 4K RL







### **Documents**

## **Product Drawings**

REC, 12P, BLK, E, ENH KEY, CAP, FLANGE, B

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_DT04-12PB-BL11\_C.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DT04-12PB-BL11\_C.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DT04-12PB-BL11\_C.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

**CONNECTOR SELECTOR** 

English

## **Product Specifications**

**Application Specification** 

English

## Agency Approvals

**UL Report** 

English